

SITOR cylindrical fuse link, 14 x 51 mm, 15 A, aR, Un AC: 690 V, Un DC: 800 V, DC acc. to UL



Figure similar

| Model | |
|--|-----------------------------|
| Product designation | SITOR cylindrical fuse link |
| Design of the product | DC acc. to UL |
| General technical data | |
| Operating class of the fuse link | aR |
| Size of the fuse link | 14x51 mm |
| Supply voltage / at DC | 700 V |
| Dissipation | |
| Power loss [W] | 5.5 W |
| Power loss [W] | 5.5 W |
| <ul style="list-style-type: none"> • for rated value of the current / at AC / in hot operating state / per pole | |
| Main circuit | |
| Operating voltage / rated value | 690 V |
| Operating current / Rated value | 15 A |
| Product details | |

| | |
|--|---------------------------|
| Product component / striker | No |
| Mounting position | Any, preferably vertical |
| Net weight | 20 g |
| Equipment marking | F F |
| <ul style="list-style-type: none"> • acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2 | |
| General Product Approval | Declaration of Conformity |



[Miscellaneous](#)



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1415>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1415>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1415

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

