

RCCB, 4-pole, type AC, In: 25 A, 30 mA, Un AC: 400 V



Model	
Product brand name	SENTRON
Product designation	RCCB
Design of the product	Instantaneous
General technical data	
Number of poles	4
Size of installation devices / acc. to DIN 43880	1
Protection against electrical shock	Finger and back-of-hand safe
Short-circuit current rating	10 kA
circuit-breaker / Design	5SV4
Mechanical service life (switching cycles) / typical	10 000
Switching function / short-term delayed	No
Overvoltage category	III
Supply voltage	
Supply voltage	
<ul style="list-style-type: none"> <li>at AC / rated value</li> <li>for testing equipment / minimum</li> </ul>	<p>400 V</p> <p>195 V</p>
Supply voltage frequency	

- rated value

50 Hz

## Protection class

### Protection class IP

IP20, if the distribution board is installed, with connected conductors

## Switching capacity

Switching capacity current / according to IEC 61008-1 / rated value

0.8 kA

## Dissipation

### Power loss [W]

- for rated value of the current / at AC / in hot operating state / per pole

1.3 W

## Electricity

### Tripping residual current / rated value

30 mA

rated current  $I_n$  / IEC, DIN/VDE / at 40 Cel

25 A

### Type of fault current

AC

Current / at AC / rated value

25 A

### $I^2t$ -value / permissible

25 410 A<sup>2</sup>·s

## Product details

Product feature / silicon-free

Yes

Product extension / can be installed / supplementary devices

Yes

## Number

Number of test cycles / for environmental testing / acc. to IEC 60068-2-30

28

## Connections

### Connectable conductor cross-section / stranded

- minimum
- maximum

0.75 mm<sup>2</sup>

35 mm<sup>2</sup>

### Connectable conductor cross-section / solid

- minimum
- maximum

0.75 mm<sup>2</sup>

35 mm<sup>2</sup>

### Tightening torque / with screw-type terminals

- minimum
- maximum

2.5 N·m

3 N·m

Position / of power supply cord

top or bottom

## Mechanical Design

### Height

90 mm

### Width

72 mm

### Depth

70 mm

### Mounting position

any

Installation depth	70 mm
Number of width units	4
Mounting type	DIN rail (REG)
Net weight	364 g

### Environmental conditions

#### Ambient temperature

- |  |        |
|--|--------|
| • minimum                              | -25 °C |
| • maximum                              | 45 °C  |
| • during storage / minimum permissible | -40 °C |
| • during storage / maximum permissible | 75 °C  |

### Certificates

#### Equipment marking

- |                          |   |
|--------------------------|---|
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

#### General Product Approval

#### Declaration of Conformity



CCC



IMQ

[Miscellaneous](#)



EG-Konf.

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5SV4342-0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV4342-0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5SV4342-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SV4342-0)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>





-CB

