

**General technical data:**

Supply voltage frequency for auxiliary and control current circuit rated value		
• minimum	Hz	50
• maximum	Hz	60
<b>Type of voltage</b>		AC/DC
<b>Control supply voltage</b>		
• at AC		
— at 50 Hz rated value		
— minimum	V	110
— maximum	V	230
— at 60 Hz rated value		
— minimum	V	110
— maximum	V	230
• at DC rated value		
— minimum	V	110
— maximum	V	230
Number of NC contacts for auxiliary contacts		0
Number of NO contacts for auxiliary contacts		0
Number of CO contacts for auxiliary contacts		0
<b>Design of the switching function positively driven</b>		No
<b>Switching behavior</b>		monostable

**Mechanical data:**

<b>Type of electrical connection</b>		screw-type terminals
<b>Design of the relay operating mechanism</b>		poled
<b>Product component Plug-in socket</b>		No
<b>Width</b>	mm	15.5

**Certificates/ approvals:**

<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>other</b>
---------------------------------	----------------------------------	--------------



[Confirmation](#)

## Further information

### **Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

### **Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=LZS:PTMG0730>

### **Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

### **Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PTMG0730>

### **Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=LZS:PTMG0730&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=LZS:PTMG0730&lang=en)

last modified:

10/24/2017