

CONNECTOR, FEMALE, 2X2-PIN, 24 V DC FOR ET200S, INTERFACE MODULE, KP32F, PN/PN COUPLER, SPRING-LOADED TERMINALS, INTERNALLY BRIDGED, COLOR-CODED AMOUNT: SEE TECHNICAL DATA



General information	
Product type designation	Connector, female, 2x2-pin
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V
Interfaces	
HMI-side interface	
<ul style="list-style-type: none"> Number of pins HMI-side 	2; Outgoing side jumpered internally, color-coded
Device-side interface	
<ul style="list-style-type: none"> Number of pins device-side 	4; Female, spring-loaded terminals 0.75 mm ²
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
China RoHS compliance	Yes
Mechanics/material	
Design of housing	plastic

Dimensions	
Width	10 mm
Height	22 mm
Thickness	25 mm
Scope of supply	
Delivery quantity in pieces	10
Other	
Merchandise	Yes
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Note:	for ET 200S, interface module, KP32F, PN-to-PN coupler
Usable in the following products	
<ul style="list-style-type: none"> • Product 1 • Product 2 • Product 3 	6AV3688-3EH47-0AX0 6ES7158-3AD00-0XA0 6ES7158-3AD01-0XA0
last modified:	11/09/2017