

SIMATIC S7-1200, Analog input, SM 1238 Energy Meter 480V AC, Energy measurement module for recording electrical parameters in 1 and 3 phase networks (TN, TT) up to 480VAC; current range: 1A, 5A; recording of voltages, currents, phase angles, power, energy values, frequencies; channel diagnosis



General information

| | |
|--|---|
| Firmware version | V2.0 |
| Product function | |
| <ul style="list-style-type: none"> • Voltage measurement • Voltage measurement with voltage transformers • Current measurement • Phase current measurement without current transformers • Phase current measurement with current transformers • Energy measurement • Frequency measurement • Power measurement • Active power measurement • Reactive power measurement • I&M data • Isochronous mode | <ul style="list-style-type: none"> Yes Yes Yes No Yes Yes Yes Yes Yes Yes Yes; I&M 0 No |
| Engineering with | |

| | |
|---|---|
| • STEP 7 TIA Portal configurable/integrated as of version | V13 SP1 |
| Operating mode | |
| • cyclic measurement | Yes |
| • acyclic measurement | Yes |
| • Acyclic measured value access | Yes |
| • Fixed measured value sets | Yes |
| • Freely definable measured value sets | Yes |
| Configuration control | |
| via dataset | Yes |
| CiR – Configuration in RUN | |
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | Yes |
| Installation type/mounting | |
| Mounting position | Horizontal, vertical |
| Supply voltage | |
| Design of the power supply | Supply via voltage measurement channel L1 |
| Type of supply voltage | AC 100 - 277 V |
| permissible range, lower limit (AC) | 90 V |
| permissible range, upper limit (AC) | 293 V |
| Line frequency | |
| • permissible range, lower limit | 47 Hz |
| • permissible range, upper limit | 63 Hz |
| Power loss | |
| Power loss, typ. | 0.6 W |
| Address area | |
| Address space per module | |
| • Address space per module, max. | 124 byte; 112 byte input / 12 byte output |
| Time of day | |
| Operating hours counter | |
| • present | Yes |
| Analog inputs | |
| Cycle time (all channels), typ. | 50 ms; Time for consistent update of all measured and calculated values (cyclic und acyclic data) |
| Interrupts/diagnostics/status information | |
| Alarms | |
| • Diagnostic alarm | Yes |
| • Limit value alarm | Yes |
| • Hardware interrupt | No |

| Diagnostics indication LED | |
|--|-------------------------|
| • Monitoring of the supply voltage (PWR-LED) | Yes |
| • Channel status display | Yes; Green LED |
| • for channel diagnostics | Yes; red Fn LED |
| • for module diagnostics | Yes; green/red DIAG LED |

Integrated Functions

Measuring functions

| | |
|---|--|
| • Measuring procedure for voltage measurement | TRMS |
| • Measuring procedure for current measurement | TRMS |
| • Type of measured value acquisition | seamless |
| • Curve shape of voltage | Sinusoidal or distorted |
| • Buffering of measured variables | Yes |
| • Parameter length | 74 byte |
| • Bandwidth of measured value acquisition | 2 kHz; Harmonics: 39 / 50 Hz, 32 / 60 Hz |

Operating mode for measured value acquisition

| | |
|---|---------------------|
| — automatic detection of line frequency | No; Parameterizable |
|---|---------------------|

Measuring range

| | |
|-------------------------------|-------|
| — Frequency measurement, min. | 45 Hz |
| — Frequency measurement, max. | 65 Hz |

Measuring inputs for voltage

| | |
|---|--|
| — Measurable line voltage between phase and neutral conductor | 277 V |
| — Measurable line voltage between the line conductors | 480 V |
| — Measurable line voltage between phase and neutral conductor, min. | 90 V |
| — Measurable line voltage between phase and neutral conductor, max. | 293 V |
| — Measurable line voltage between the line conductors, min. | 155 V |
| — Measurable line voltage between the line conductors, max. | 508 V |
| — Measurement category for voltage measurement in accordance with IEC 61010-2-030 | CAT II; CAT III in case of guaranteed protection level of 1.5 kV |
| — Internal resistance line conductor and neutral conductor | 3.4 MΩ |
| — Power consumption per phase | 20 mW |
| — Impulse voltage resistance 1,2/50μs | 1 kV |

Measuring inputs for current

| | |
|--|--|
| — measurable relative current (AC), min. | 1 %; Relative to the secondary rated current 5 A |
| — measurable relative current (AC), max. | 100 %; Relative to the secondary rated current 5 A |

| | |
|--|--|
| — Continuous current with AC, maximum permissible | 5 A |
| — Apparent power consumption per phase for measuring range 5 A | 0.6 V·A |
| — Rated value short-time withstand current restricted to 1 s | 100 A |
| — Input resistance measuring range 0 to 5 A | 25 mΩ; At the terminal |
| — Zero point suppression | Parameterizable: 2 ... 250 mA, default 50 mA |
| — Surge strength | 10 A; for 1 minute |

Accuracy class according to IEC 61557-12

| | |
|-------------------------------------|-----------------------------------|
| — Measured variable voltage | 0,2 |
| — Measured variable current | 0,2 |
| — Measured variable apparent power | 0.5 |
| — Measured variable active power | 0.5 |
| — Measured variable reactive power | 1 |
| — Measured variable power factor | 0.5 |
| — Measured variable active energy | 0.5 |
| — Measured variable reactive energy | 1 |
| — Measured variable neutral current | 0.5; calculated |
| — Measured variable phase angle | ±1 °; not covered by IEC 61557-12 |
| — Measured variable frequency | 0.05 |

Potential separation

Potential separation channels

- between the channels and backplane bus Yes; 3 700V AC (type test) CAT III

Isolation

Isolation tested with 2 300V AC for 1 min. (type test)

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. -20 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -20 °C
- vertical installation, max. 50 °C

Dimensions

| | |
|--------|--------|
| Width | 45 mm |
| Height | 100 mm |
| Depth | 75 mm |

Weights

Weight (without packaging) 165 g

Other

Data for selecting a current transformer

- Burden power current transformer x/1A, min.
- Burden power current transformer x/5A, min.

As a function of cable length and cross section, see device manual

As a function of cable length and cross section, see device manual

last modified:

11/28/2017