



SIMATIC S7-1500, Analog input module AI 8xU/R/RTD/TC HF, 16 bit resolution, up to 21 bit Resolution at RT and TC, Accuracy 0.1%, 8 channels in groups of 1, Common mode voltage: 30V AC/60V DC, diagnostics; Hardware interrupts scalable Temperature range, Thermocouple type C: Calibrate in RUN incl. infeed element, Shield bracket and shield terminal

| General information | |
|---|--------------------|
| Product type designation | AI 8xU/R/RTD/TC HF |
| HW functional status | FS01 |
| Firmware version | V1.1.0 |
| <ul style="list-style-type: none"> FW update possible | Yes |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> Measuring range scalable | Yes |
| <ul style="list-style-type: none"> Scalable measured values | No |
| <ul style="list-style-type: none"> Adjustment of measuring range | No |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version | V14 / - |
| <ul style="list-style-type: none"> STEP 7 configurable/integrated as of version | V5.5 SP3 / - |
| <ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision | V1.0 / V5.1 |
| <ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision | V2.3 / - |
| Operating mode | |
| <ul style="list-style-type: none"> Oversampling | No |
| <ul style="list-style-type: none"> MSI | Yes |

| CiR – Configuration in RUN | |
|---|--|
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | Yes |
| Supply voltage | |
| Type of supply voltage | DC |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 55 mA; with 24 V DC supply |
| Power | |
| Power available from the backplane bus | 0.85 W |
| Power loss | |
| Power loss, typ. | 1.9 W |
| Analog inputs | |
| Number of analog inputs | 8; Plus one additional RTD (reference) channel |
| <ul style="list-style-type: none"> • For voltage measurement | 8; Plus one additional RTD (reference) channel |
| <ul style="list-style-type: none"> • For resistance/resistance thermometer measurement | 8; Plus one additional RTD (reference) channel |
| <ul style="list-style-type: none"> • For thermocouple measurement | 8; Plus one additional RTD (reference) channel |
| permissible input voltage for voltage input (destruction limit), max. | 20 V |
| Constant measurement current for resistance-type transmitter, typ. | 150 Ohm, 300 Ohm, 600 Ohm, Cu10, Cu50, Cu100, Ni10, Ni100, Ni120, Ni200, Pt10, Pt50, Pt100, Pt200 climate: 1 mA; 6 kOhm, Ni500, Ni1000, LG-Ni1000, Pt200 standard, Pt500, Pt1000, PTC: 0.25 mA |
| Technical unit for temperature measurement adjustable | Yes; °C/°F/K |
| Input ranges (rated values), voltages | |
| <ul style="list-style-type: none"> • 0 to +5 V | No |
| <ul style="list-style-type: none"> • 0 to +10 V | No |
| <ul style="list-style-type: none"> • 1 V to 5 V | No |
| <ul style="list-style-type: none"> • -1 V to +1 V | Yes |
| <ul style="list-style-type: none"> • Input resistance (-1 V to +1 V) | 10 MΩ |
| <ul style="list-style-type: none"> • -10 V to +10 V | No |
| <ul style="list-style-type: none"> • -2.5 V to +2.5 V | No |
| <ul style="list-style-type: none"> • -25 mV to +25 mV | Yes |
| <ul style="list-style-type: none"> • Input resistance (-25 mV to +25 mV) | 10 MΩ |
| <ul style="list-style-type: none"> • -250 mV to +250 mV | Yes |
| <ul style="list-style-type: none"> • Input resistance (-250 mV to +250 mV) | 10 MΩ |

| | |
|--|-----------------------|
| • -5 V to +5 V | No |
| • -50 mV to +50 mV | Yes |
| • Input resistance (-50 mV to +50 mV) | 10 MΩ |
| • -500 mV to +500 mV | Yes |
| • Input resistance (-500 mV to +500 mV) | 10 MΩ |
| • -80 mV to +80 mV | Yes |
| • Input resistance (-80 mV to +80 mV) | 10 MΩ |
| Input ranges (rated values), currents | |
| • 0 to 20 mA | No |
| • -20 mA to +20 mA | No |
| • 4 mA to 20 mA | No |
| Input ranges (rated values), thermocouples | |
| • Type B | Yes |
| • Input resistance (Type B) | 10 MΩ |
| • Type C | Yes |
| • Input resistance (Type C) | 10 MΩ |
| • Type E | Yes |
| • Input resistance (Type E) | 10 MΩ |
| • Type J | Yes |
| • Input resistance (type J) | 10 MΩ |
| • Type K | Yes |
| • Input resistance (Type K) | 10 MΩ |
| • Type L | No |
| • Type N | Yes |
| • Input resistance (Type N) | 10 MΩ |
| • Type R | Yes |
| • Input resistance (Type R) | 10 MΩ |
| • Type S | Yes |
| • Input resistance (Type S) | 10 MΩ |
| • Type T | Yes |
| • Input resistance (Type T) | 10 MΩ |
| • Type TXK/TXK(L) to GOST | Yes |
| • Input resistance (Type TXK/TXK(L) to GOST) | 10 MΩ |
| Input ranges (rated values), resistance thermometer | |
| • Cu 10 | Yes; Standard/climate |
| • Input resistance (Cu 10) | 10 MΩ |
| • Cu 10 according to GOST | Yes; Standard/climate |
| • Input resistance (Cu 10 according to GOST) | 10 MΩ |
| • Cu 50 | Yes; Standard/climate |
| • Input resistance (Cu 50) | 10 MΩ |
| • Cu 50 according to GOST | Yes; Standard/climate |

| | |
|--|-----------------------|
| • Input resistance (Cu 50 according to GOST) | 10 MΩ |
| • Cu 100 | Yes; Standard/climate |
| • Input resistance (Cu 100) | 10 MΩ |
| • Cu 100 according to GOST | Yes; Standard/climate |
| • Input resistance (Cu 100 according to GOST) | 10 MΩ |
| • Ni 10 | Yes; Standard/climate |
| • Input resistance (Ni 10) | 10 MΩ |
| • Ni 10 according to GOST | Yes; Standard/climate |
| • Input resistance (Ni 10 according to GOST) | 10 MΩ |
| • Ni 100 | Yes; Standard/climate |
| • Input resistance (Ni 100) | 10 MΩ |
| • Ni 100 according to GOST | Yes; Standard/climate |
| • Input resistance (Ni 100 according to GOST) | 10 MΩ |
| • Ni 1000 | Yes; Standard/climate |
| • Input resistance (Ni 1000) | 10 MΩ |
| • Ni 1000 according to GOST | Yes; Standard/climate |
| • Input resistance (Ni 1000 according to GOST) | 10 MΩ |
| • LG-Ni 1000 | Yes; Standard/climate |
| • Input resistance (LG-Ni 1000) | 10 MΩ |
| • Ni 120 | Yes; Standard/climate |
| • Input resistance (Ni 120) | 10 MΩ |
| • Ni 120 according to GOST | Yes; Standard/climate |
| • Input resistance (Ni 120 according to GOST) | 10 MΩ |
| • Ni 200 | Yes; Standard/climate |
| • Input resistance (Ni 200) | 10 MΩ |
| • Ni 200 according to GOST | Yes; Standard/climate |
| • Input resistance (Ni 200 according to GOST) | 10 MΩ |
| • Ni 500 | Yes; Standard/climate |
| • Input resistance (Ni 500) | 10 MΩ |
| • Ni 500 according to GOST | Yes; Standard/climate |
| • Input resistance (Ni 500 according to GOST) | 10 MΩ |
| • Pt 10 | Yes; Standard/climate |
| • Input resistance (Pt 10) | 10 MΩ |
| • Pt 10 according to GOST | Yes; Standard/climate |
| • Input resistance (Pt 10 according to GOST) | 10 MΩ |
| • Pt 50 | Yes; Standard/climate |
| • Input resistance (Pt 50) | 10 MΩ |
| • Pt 50 according to GOST | Yes; Standard/climate |
| • Input resistance (Pt 50 according to GOST) | 10 MΩ |
| • Pt 100 | Yes; Standard/climate |
| • Input resistance (Pt 100) | 10 MΩ |

| | |
|---|---|
| • Pt 100 according to GOST | Yes; Standard/climate |
| • Input resistance (Pt 100 according to GOST) | 10 MΩ |
| • Pt 1000 | Yes; Standard/climate |
| • Input resistance (Pt 1000) | 10 MΩ |
| • Pt 1000 according to GOST | Yes; Standard/climate |
| • Input resistance (Pt 1000 according to GOST) | 10 MΩ |
| • Pt 200 | Yes; Standard/climate |
| • Input resistance (Pt 200) | 10 MΩ |
| • Pt 200 according to GOST | Yes; Standard/climate |
| • Input resistance (Pt 200 according to GOST) | 10 MΩ |
| • Pt 500 | Yes; Standard/climate |
| • Input resistance (Pt 500) | 10 MΩ |
| • Pt 500 according to GOST | Yes; Standard/climate |
| • Input resistance (Pt 500 according to GOST) | 10 MΩ |
| Input ranges (rated values), resistors | |
| • 0 to 150 ohms | Yes |
| • Input resistance (0 to 150 ohms) | 10 MΩ |
| • 0 to 300 ohms | Yes |
| • Input resistance (0 to 300 ohms) | 10 MΩ |
| • 0 to 600 ohms | Yes |
| • Input resistance (0 to 600 ohms) | 10 MΩ |
| • 0 to 3000 ohms | No |
| • 0 to 6000 ohms | Yes |
| • Input resistance (0 to 6000 ohms) | 10 MΩ |
| • PTC | Yes |
| • Input resistance (PTC) | 10 MΩ |
| Thermocouple (TC) | |
| Temperature compensation | |
| — parameterizable | Yes |
| — internal temperature compensation | Yes |
| — external temperature compensation via RTD | Yes |
| — Compensation for 0 °C reference point temperature | Yes; fixed value can be set |
| — Reference channel of the module | Yes; 9th channel that can be used as a genuine 9th RTD channel regardless of the parameterization of the other channels, or that can be used for compensation in the case of TC measurement |
| Cable length | |
| • shielded, max. | 800 m; at U; 200 m at R/RTD/TC |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |

- Resolution with overrange (bit including sign), max.
- Integration time, parameterizable
- Integration time (ms)
- Basic conversion time, including integration time (ms)
 - additional conversion time for wire-break monitoring
- Interference voltage suppression for interference frequency f1 in Hz
- Basic execution time of the module (all channels released)

21 bit; For measuring mode RTC and TC when using the function "Scalable temperature measuring range" (32 bit REAL format); 16 bit for measuring mode R and U; 16 bit for all measuring modes when using the S7 format (16 bit INTEGER)

Yes

Fast mode: 2.5 / 16.67 / 20 / 100 ms, standard mode: 7.5 / 50 / 60 / 300 ms

Fast mode: 4 / 18 / 22 / 102 ms; Standard mode: 9 / 52 / 62 / 302 ms

Thermocouples, 150 Ohm, 300 Ohm, 600 Ohm, Cu10, Cu50, Cu100, Ni10, Ni100, Ni120, Ni200, Pt10, Pt50, Pt100: 4 ms; 6 kOhm, Ni500, Ni1000, LG-Ni1000, Pt200, Pt500, Pt1000: 13 ms
400 / 60 / 50 / 10 Hz

Corresponds to the channel with the highest basic conversion time

Smoothing of measured values

- parameterizable
- Step: None
- Step: low
- Step: Medium
- Step: High

Yes

Yes

Yes

Yes

Yes

Encoder

Connection of signal encoders

- for voltage measurement
- for current measurement as 2-wire transducer
- for current measurement as 4-wire transducer
- for resistance measurement with two-wire connection
- for resistance measurement with three-wire connection
- for resistance measurement with four-wire connection

Yes

No

No

Yes

Yes; All measuring ranges except PTC; internal compensation of the cable resistances

Yes; All measuring ranges except PTC

Errors/accuracies

| | |
|---|-----------|
| Linearity error (relative to input range), (+/-) | 0.02 % |
| Temperature error (relative to input range), (+/-) | 0.005 %/K |
| Crosstalk between the inputs, max. | -80 dB |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-) | 0.02 % |
| Temperature error of internal compensation | ±1,5 °C |

Operational error limit in overall temperature range

- Voltage, relative to input range, (+/-) 0.1 %
- Resistance, relative to input range, (+/-) 0.1 %

- Resistance thermometer, relative to input range, (+/-)
- Thermocouple, relative to input range, (+/-)

Cuxxx Standard: ±0.5 K, Cuxxx Klima: ±0.5 K, Ptxxx Standard: ±1 K, Ptxxx Klima: ±0.5 K, Nixxx Standard: ±0.5 K, Nixxx Klima: ±0.3 K

Type B: > 600 °C ±2 K, Type E: > -200 °C ±1 K, Type J: > -210 °C ±1 K, Type K: > -200 °C ±2 K, Type N: > -200 °C ±2 K, Type R: > 0 °C ±2 K, Type S: > 0 °C ±2 K, Type T: > -200 °C ±1 K, Type C: ±4 K, Type TXK/TXK(L): ±1 K

Basic error limit (operational limit at 25 °C)

- Voltage, relative to input range, (+/-)
- Resistance, relative to input range, (+/-)
- Resistance thermometer, relative to input range, (+/-)
- Thermocouple, relative to input range, (+/-)

0.05 %

0.05 %

Cuxxx Standard: ±0.3 K, Cuxxx Klima: ±0.2 K, Ptxxx Standard: ±0.5 K, Ptxxx Klima: ±0.2 K, Nixxx Standard: ±0.3 K, Nixxx Klima: ±0.15 K

Type B: > 600 °C ±1 K, Type E: > -200 °C ±0.5 K, Type J: > -210 °C ±0.5 K, Type K: > -200 °C ±1 K, Type N: > -200 °C ±1 K, Type R: > 0 °C ±1 K, Type S: > 0 °C ±1 K, Type T: > -200 °C ±0.5 K, Type C: ±2 K, Type TXK/TXK(L): ±0.5 K

Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency

- Series mode interference (peak value of interference < rated value of input range), min.
- Common mode voltage, max.
- Common mode interference, min.

80 dB; in the Standard operating mode, 40 dB in the Fast operating mode

60 V DC/30 V AC

80 dB

Isochronous mode

Isochronous operation (application synchronized up to terminal)

No

Interrupts/diagnostics/status information

Diagnostics function

Yes

Alarms

- Diagnostic alarm
- Limit value alarm

Yes

Yes; two upper and two lower limit values in each case

Diagnostic messages

- Monitoring the supply voltage
- Wire-break
- Overflow/underflow

Yes

Yes; Only with TC, R, RTD

Yes

Diagnostics indication LED

- RUN LED
- ERROR LED
- Monitoring of the supply voltage (PWR-LED)
- Channel status display
- for channel diagnostics
- for module diagnostics

Yes; Green LED

Yes; Red LED

Yes; Green LED

Yes; Green LED

Yes; Red LED

Yes; Red LED

Potential separation

Potential separation channels

- between the channels
- between the channels, in groups of
- between the channels and backplane bus
- between the channels and the power supply of the electronics

Yes
1
Yes
Yes

Permissible potential difference

between different circuits

60 V DC/30 V AC; insulation rated for 120 V AC basic insulation: between the channels and the supply voltage L+; between the channels and the backplane bus; between the channels

Isolation

Isolation tested with

2 000 V DC between the channels and the supply voltage L+; 2 000 V DC between the channels and the backplane bus; 2 000 V DC between the channels; 707 V DC (type test) between the supply voltage L+ and the backplane bus

Standards, approvals, certificates

Suitable for applications according to AMS 2750

Yes; Declaration of Conformity, see online support entry 109757262

Suitable for applications according to CQI-9

Yes; Based on AMS 2750 E

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. 0 °C
- horizontal installation, max. 60 °C
- vertical installation, min. 0 °C
- vertical installation, max. 40 °C

Decentralized operation

Prioritized startup

Yes

Dimensions

Width

35 mm

Height

147 mm

Depth

129 mm

Weights

Weight, approx.

290 g

Other

Note:

For the R/RDT three-wire measurement, the conductor compensation is made alternating with the measurement. This then requires two module cycles for a measured value.

last modified:

08/13/2018