

OFF switch 20 A 2 NO



Model	
Product brand name	SENTRON
Product designation	On/Off switches
Design of the switching function	Off switches
General technical data	
Number of poles	1
Short-circuit current rating	10 kA
Supply voltage	
Type of voltage	AC
Protection class	
Protection class IP	Other
Switching capacity	
Switching capacity current / rated value	0.06 kA
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	0.7 W
Main circuit	

Operating voltage / rated value	400 V
Operating current / rated value	20 A

Product details

Product component / Signal lamp	No
---------------------------------	----

Product function

Product function / positive opening (acc. to DIN VDE 0113)	No
--	----




Number

Number of NO contacts	2
Connectable conductor cross-section	1 ... 6 mm ²
<ul style="list-style-type: none"> • for flexible conductor / with core end processing 	
<ul style="list-style-type: none"> • for rigid conductor 	
Tightening torque / with screw-type terminals	0.8 ... 1 N·m

Mechanical Design

Height	90 mm
Depth	77 mm
Installation depth	70 mm
Number of width units	1
Net weight	75 g

Certificates

General Product Approval	Declaration of Conformity	Test Certificates	other
 CCC	 VDE	 EG-Konf.	Type Test Certificates/Test Report Miscellaneous Environmental Confirmations

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TE8112>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TE8112>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE8112

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

