

Product type designation

CP 1243-7 LTE EU

Communications processor CP 1243-7 LTE EU for Connection of SIMATIC S7-1200 to LTE network in European Frequency range



Transmission rate

Transfer rate

- for LTE transmission
 - with downlink / maximum 42 Mbit/s
 - with uplink / maximum 5.76 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections	
<ul style="list-style-type: none"> • for external antenna(s) 1 • for power supply 1 	
Number of slots	
<ul style="list-style-type: none"> • for SIM cards 1 	
Type of electrical connection	
<ul style="list-style-type: none"> • for external antenna(s) SMA socket (50 ohms) • for power supply 3-pole terminal block 	
Slot version	
<ul style="list-style-type: none"> • for SIM card Standard 	

Wireless technology

Type of mobile wireless service	
<ul style="list-style-type: none"> • is supported / SMS 	Yes
<ul style="list-style-type: none"> • is supported / GPRS 	Yes
<ul style="list-style-type: none"> • Note 	GPRS (Multislot Class 10)
Type of mobile network / is supported	
<ul style="list-style-type: none"> • GSM 	Yes
<ul style="list-style-type: none"> • UMTS 	Yes
<ul style="list-style-type: none"> • LTE 	Yes
Operating frequency	
<ul style="list-style-type: none"> • for GSM transmission / 900 MHz 	Yes
<ul style="list-style-type: none"> • for GSM transmission / 1800 MHz 	Yes
<ul style="list-style-type: none"> • with UMTS transmission / 900 MHz 	Yes
<ul style="list-style-type: none"> • with UMTS transmission / 2100 MHz 	Yes
<ul style="list-style-type: none"> • for LTE transmission / 800 MHz 	Yes
<ul style="list-style-type: none"> • for LTE transmission / 1800 MHz 	Yes
<ul style="list-style-type: none"> • for LTE transmission / 2600 MHz 	Yes

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	20 %
Consumed current	
<ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / typical 	0.1 A
<ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / maximum 	0.22 A
Ambient temperature	
<ul style="list-style-type: none"> • for vertical installation / during operation 	-20 ... +60 °C
<ul style="list-style-type: none"> • for horizontally arranged busbars / during operation 	-20 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	100 mm

Depth	75 mm
Net weight	0.133 kg
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	No
<ul style="list-style-type: none"> • wall mounting 	Yes

Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> • per CPU / maximum 	3

Performance data

Number of users/telephone numbers / definable / maximum	10
---	----

Performance data / open communication

Number of possible connections / for open communication	
<ul style="list-style-type: none"> • by means of T blocks / maximum 	like CPU

Performance data / IT functions

Number of possible connections	
<ul style="list-style-type: none"> • as e-mail client / maximum 	1

Performance data / telecontrol

Suitability for use	
<ul style="list-style-type: none"> • substation 	Yes
Control center connection	Telecontrol Server Basic supported
<ul style="list-style-type: none"> • by means of a permanent connection 	supported
<ul style="list-style-type: none"> • by means of demand-oriented connection 	supported
<ul style="list-style-type: none"> • Note 	Connection to SCADA system using OPC interface
Protocol / is supported	
<ul style="list-style-type: none"> • DNP3 	No
<ul style="list-style-type: none"> • IEC 60870-5 	No
Product function / data buffering if connection is aborted	Yes; 64,000 values
Number of stations / for direct communication / with Telecontrol Server Basic	
<ul style="list-style-type: none"> • in send direction / maximum 	3
<ul style="list-style-type: none"> • in receive direction / maximum 	15

Performance data / Teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
Product function	
<ul style="list-style-type: none"> • program download with SIMATIC STEP 7 	Yes
<ul style="list-style-type: none"> • Remote firmware update 	Yes

Product functions / management, configuration

Configuration software

- required

STEP 7 Basic/Professional

Product functions / Diagnosis

Product function / Web-based diagnostics

Yes

Product functions / Security

Firewall version

stateful inspection

Product function / with VPN connection

IPSec, SINEMA RC

Type of encryption algorithms / with VPN connection

AES-256, AES-192, AES-128, 3DES-168, DES-56

Type of authentication procedure / with VPN connection

Preshared key (PSK), X.509v3 certificates

Type of hashing algorithms / with VPN connection

MD5, SHA-1

Number of possible connections / with VPN connection

1

Product function

- password protection for teleservice access
- encrypted data transmission

Yes

Yes

Product functions / Time

Protocol / is supported

- NTP

Yes

time synchronization

- from control center

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/03/2019