

SENTRON, cylindrical fuse link, 10 x 38 mm, 10 A, aM, Un AC: 500 V



| Model | |
|---|--------------------------|
| Product brand name | SENTRON |
| Product designation | Cylindrical fuse link |
| General technical data | |
| Operating class of the fuse link | aM |
| Size of the fuse link | 10x38 mm |
| Type of voltage | AC |
| Current / at AC / rated value | 10 A |
| Supply voltage / at DC | 250 V |
| Operating voltage / rated value | 500 V |
| Dissipation | |
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 0.6 W |
| Main circuit | |
| Operating current / Rated value | 10 A |
| Product details | |
| Product component / striker | No |
| Mounting position | Any, preferably vertical |

Net weight

7 g

Certificates

Reference code

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

F

F

Declaration of Conformity

Test Certificates



EG-Konf.

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW8003-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NW8003-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW8003-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

