SIEMENS

Data sheet

6GK1907-0AB11-6AA0

Product type designation Product description

Power Plug PRO (Push Pull)

Power connector, 5-pole Power Plug PRO 5-pole Push Pull Power connector with Metal housing for on-site mounting (Packaging unit 1 connector)



Suitability for use	Field-assembly connector (spring-loaded contacts for 5-core power lines) for push-pull device connection in high degree of protection, for voltage supply with 2 x 24 V DC (metal housing)	
Interfaces		
Number of electrical connections		
 for network components or terminal equipment 	1	
Type of electrical connection		
 for network components or terminal equipment 	Power contacts (Push Pull casing)	
Type of electrical connection / FastConnect	No	
Mechanical data		
Material / of the enclosure	metal	
Locking mechanism design	Push-pull	
Design, dimensions and weight		
Type of cable outlet	180° cable outlet	
Width	36 mm	
Height	30 mm	
Depth	66.3 mm	

Net weight	83.1 g
Permitted ambient conditions	
Ambient temperature	
 during operation 	-40 +85 °C
• during storage	-40 +85 °C
• during transport	-40 +85 °C
Chemical resistance / to water	resistant
Protection class IP	IP65/67
Product properties, functions, components / general	
Product feature	
• silicon-free	Yes
Product component	
• strain relief	Yes
Standards, specifications, approvals	
Certificate of suitability	
 RoHS conformity 	Yes
• UL approval	Yes
 Railway application in accordance with EN 50155 	No
Further Information / Internet Links	
Internet-Link	
 to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com
last modified:	08/27/2019