

HSK-M-Flex-EMC


Metr., Metr.-dlouhá



Materiál	poniklovaná mosaz
Ochranná pružina	INOX 1.4310
Vložka	polyamid
Tvarové těsnění	NBR
O-kroužek	NBR
Krytí	IP 68 – 10 bar / IP 69K
Pracovní teplota	-40 °C – 100 °C



// Jiný těsnicí materiál např. silikon na poptávku



AG	\varnothing mm	d mm	H mm	\varnothing mm	GL mm	Obj. č.	GL mm	Obj. č. dlouhá
M 12 x 1,5	3–6,5	6,8	55	14	6,5	1.624.1200.50	10	1.624.1200.30
M 12 x 1,5	2–5	6,8	55	14	6,5	1.624.1200.51	10	1.624.1200.31
M 16 x 1,5	5–10	10,3	77	20	6	1.624.1600.50	10	1.624.1600.30
M 16 x 1,5	3–7	10,3	77	20	6	1.624.1600.51	10	1.624.1600.31
M 20 x 1,5	10–14	14,3	98	24	6	1.624.2000.50	10	1.624.2000.30
M 20 x 1,5	7–12	14,3	98	24	6	1.624.2000.51	10	1.624.2000.31
M 25 x 1,5	13–18	18,4	111	30	7	1.624.2500.50	12	1.624.2500.30
M 25 x 1,5	9–16	18,4	111	30	7	1.624.2500.51	12	1.624.2500.31

