

Lightning conductor T1/T2, UN 240/400 V, UC 335/264 V A.C.,  
pluggable protective modules, 3+1 circuit (TN-S, TT), Width 72 mm



Article number

General data	
standard	IEC 61643-11: 2011, EN 61643-11: 2012
product designation	Surge protection device
SPD classification / acc. to EN 61643-11	
• Test Class I, Type 1	Yes
• Test Class II, Type 2	Yes
• Test Class III, Type 3	No
number of SPD ports	1
Product version	Combination surge arresters
design of pole	3+N/PE
designation of the protective paths	L-N, L-PE, N-PE
Accessories	3 x 5SD7414-3 + 1 x 5SD7414-2
mounting type	DIN rail NS 35
material / of the enclosure	PA 6.6 / PBT
size of surge arrester	4 TE
Degree of pollution	2
overvoltage category / acc. to IEC 61010-1	III
protection class IP / at connection all terminals	IP20

shock acceleration	30 gn
vibrational acceleration / at 5 Hz ... 500 Hz / limited to 2,5 h / per axis	7.5 gn
Numerische Liste	-40 °C ... 80 °C
ambient temperature / during storage and transport	-40 °C ... 80 °C
relative humidity / during operation	5 % ... 95 %
installation altitude / at height above sea level / maximum	2 000 m
Width	71.2 mm
Height	89.9 mm
depth	77.5 mm
net weight	634 g

### Electrical data

type of distribution system	TT, TN-S
operating voltage	240 / 415 V AC
operating voltage	230 V
operating frequency	50/60 Hz
continuous operating voltage	
• maximum	335 V
• between N and PE	264 V
• between L and (PE)N	335 V
load current	80 A
protective conductor current	5 µA (255 V AC)
apparent power consumption / maximum	810 mVA
discharge current	
• between L and (PE)N / at (8/20) µs	12.5 kA
• between L and N / at (8/20) µs	50 kA
• between L and PE / at (8/20) µs	50 kA
• between L and PE / at (8/20) µs	12.5 kA
• between N and PE / at (8/20) µs	50 kA
• between N and PE / at (8/20) µs	50 kA
total discharge current / at (8/20) µs	50 kA
total lightning impulse current / at (10/350) µs	50 kA
lightning current peak value / at (10/350) µs	
• lightning current peak value / between L and PE	12.5 kA
• lightning current peak value / between N and PE	50 kA
• lightning current peak value / between L and N	12.5 kA
charge of the lightning surge / at (10/350) µs	
• charge of the lightning surge / between L and N	6.25 A·s
• charge of the lightning surge / between L and PE	6.25 A·s

<ul style="list-style-type: none"> <li>• charge of the lightning surge / between N and PE</li> </ul>	25 A·s
follow current extinguishing capability	
<ul style="list-style-type: none"> <li>• between N and PE</li> </ul>	100 A (264 V a.c.)
short-circuit rating (SCCR) / at 264 V	25 kA
protection level	
<ul style="list-style-type: none"> <li>• between L and N</li> </ul>	1.2 kV
<ul style="list-style-type: none"> <li>• between L and PE</li> </ul>	2 kV
<ul style="list-style-type: none"> <li>• between N and L</li> </ul>	1.2 kV
<ul style="list-style-type: none"> <li>• between N and PE</li> </ul>	1.7 kV
<ul style="list-style-type: none"> <li>• between PE and N and/or L</li> </ul>	1.7 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and (PE)N / at rated value of discharge current / maximum</li> </ul> </li> </ul>	1.2 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and (PE)N / at 10 kA / maximum</li> </ul> </li> </ul>	1.1 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and (PE)N / at 5 kA / maximum</li> </ul> </li> </ul>	1 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and (PE)N / at 3 kA / maximum</li> </ul> </li> </ul>	0.9 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and PE / at rated value of discharge current / maximum</li> </ul> </li> </ul>	2 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and PE / at 10 kA / maximum</li> </ul> </li> </ul>	1.5 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and PE / at 5 kA / maximum</li> </ul> </li> </ul>	1.2 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between L and PE / at 3 kA / maximum</li> </ul> </li> </ul>	1.1 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between N and PE / at rated value of discharge current / maximum</li> </ul> </li> </ul>	0.6 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between N and PE / at 10 kA / maximum</li> </ul> </li> </ul>	0.5 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between N and PE / at 5 kA / maximum</li> </ul> </li> </ul>	0.5 kV
<ul style="list-style-type: none"> <li>•           <ul style="list-style-type: none"> <li>— residual voltage / between N and PE / at 3 kA / maximum</li> </ul> </li> </ul>	0.4 kV
response value of the surge voltage / at 6 kV / at (1.2/50) μs	
<ul style="list-style-type: none"> <li>• between N and PE</li> </ul>	1.7 kV
<ul style="list-style-type: none"> <li>• response time / between L and (PE)N</li> </ul>	25 ns
<ul style="list-style-type: none"> <li>• response time / between N and PE</li> </ul>	100 ns
adjustable response factor / of trip current	1.6

fuse protection type / at V-shaped connection	80 A AC (gG)
fuse protection type / for T-connector	160 A AC (gG)

### Connections/ Terminals

type of electrical connection	Screw terminal
wire stripping length	16 mm
tightening torque	4.3 ... 4.7
wire stripping length	16 mm
connectable conductor cross-section	
• for finely stranded conductor	1.5 ... 25
• for rigid conductor	1.5 ... 35
• finely stranded	1.5 ... 25
AWG number / as coded connectable conductor cross section	15 ... 2
design of the thread / of the connection screw	M5
signal design	optical

### NEMA/UL - Data

type of distribution system	TT, TN-S
TOV behavior	
• at TOV test voltage (L-N)	415 V AC (5 s / withstand mode)
• at TOV test voltage (N-PE)	1200 V (200 ms / withstand mode)
combustibility class acc. to UL 94	V0

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SD7414-2>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SD7414-2>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SD7414-2](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7414-2)

**CAX-Online-Generator**

<http://www.siemens.com/cax>



