

product type designation



Antenna ANT795-6MP

ANT795-6MP WLAN antenna with omnidirectional characteristic incl. N-female connector: 5/7 dBi; IP65/67 (-40 - +80 °C); 2.4/5 GHz Wi-Fi compliance and national approvals to be observed; Mounting on wall or mast; compact instructions in German/English Scope of delivery: 1x ANT795-6MP, 1 x mounting aid

radio frequencies	
type of wireless network / is supported	WLAN
operating frequency	2.4 ... 2.5 GHz
<ul style="list-style-type: none"> for WLAN in 2.4 GHz frequency band for WLAN in 5 GHz frequency band 1 	4.94 ... 5.925 GHz
electrical data	
impedance	50 Ω
polarization	linear vertical
radiation characteristic	omnidirectional
antenna gain compared to spherical radiator	5 dB
<ul style="list-style-type: none"> of the WLAN antenna / in the 2.4 GHz frequency band of the WLAN antenna / in the 5 GHz frequency band 	7 dB
standing wave ratio (VSWR) / maximum	2
radiating angle of the antenna	360°
<ul style="list-style-type: none"> in the 2.4 GHz frequency band / horizontal in the 2.4 GHz frequency band / vertical in the 5 GHz frequency band / horizontal in the 5 GHz frequency band / vertical 	25° 360° 15°; take the antenna diagram into account regarding the horizontal beam angle
number of electrical connections / of the antenna	1
type of electrical connection / of the antenna	N-Connector
design of plug-in connection	female
angle of inclination / downward / maximum	0°
mechanical data	
material	UV-resistant white plastic
<ul style="list-style-type: none"> of outer shell 	
ambient conditions	
ambient temperature	-40 ... +80 °C
<ul style="list-style-type: none"> during operation during storage during transport 	-40 ... +80 °C -40 ... +80 °C -40 ... +80 °C
protection class IP	IP65 / 67
wind load / maximum	19.6 N
resistance to salt-laden atmosphere / conformity acc. to EN 60068-2-52	Yes; Severity 1
design, dimensions and weights	

width	97 mm
height	367 mm; incl. bracket
depth	64 mm
diameter	28.6 mm
net weight	300 g
fastening method	
• mast mounting	Yes
• wall mounting	Yes
• roof mounting	No
• directly on the device	No
product features, product functions, product components / general	
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
product conformity	UL 94-HB
wireless approval	Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	12/16/2020 