



SITOP SEL1200/4X2-10A

SITOP SEL1200 10 A Selectivity module 4-channel with switching characteristic Input: 24 V DC/40 A Output: 24 V DC/4x 10 A Threshold value adjustable 2-10 A With monitoring interface

Input	
type of the power supply network	Controlled DC voltage
supply voltage / at DC / rated value	24 V
input voltage / at DC	20,4 ... 30 V
overvoltage overload capability	35 V
input current / at rated input voltage 24 V / rated value	40 A
Output	
voltage curve / at output	controlled DC voltage
formula for output voltage	$V_{in} - \text{approx. } 0.2 \text{ V}$
relative overall tolerance / of the voltage / note	In accordance with the supplying input voltage
number of outputs	4
output current / up to 60 °C / per output / rated value	10 A
adjustable current response value current / of the current-dependent overload release	2 ... 10 A
type of response value setting	via potentiometer
product feature	
<ul style="list-style-type: none"> parallel switching of outputs bridging of equipment 	Yes No
type of outputs connection	Connection of all outputs after ramp-up of the supply voltage > 20 V; delay time of 25 ms, 200 ms, 500 ms or "load-optimized" can be set via DIP switch for sequential connection
Efficiency	
efficiency in percent	98 %
power loss [W] / at rated output voltage / for rated value of the output current / typical	10 W
Switch-off characteristic per output	
switching characteristic	
<ul style="list-style-type: none"> of the excess current of the immediate switch-off 	$I_{out} > 2.0 \times \text{set value}$, switch-off after approx. 30 ms, $I_{out} > 1.8 \times \text{set value}$, switch-off after approx. 0.1 s, $I_{out} > 1.5 \times \text{set value}$, switch-off after approx. 1 s, $I_{out} > 1.0 \times \text{set value}$, switch-off after approx. 5 s $I_{out} > \text{set value}$ and $V_{in} < 20 \text{ V}$, switch-off after approx. 8 ms
design of the reset device/resetting mechanism	via sensor per output
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
Protection and monitoring	

fuse protection type / at input	16 A per output (not accessible)
display version / for normal operation	Three-color LED per output: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"
design of the switching contact / for signaling function	Floating common signal contact or status signal output (pulse/pause signal that can be evaluated via SIMATIC function block)
Safety	
galvanic isolation / between input and output at switch-off	No
standard / for safety	according to EN 60950-1 and EN 50178
operating resource protection class	Class III
protection class IP	IP20
Approvals	
certificate of suitability <ul style="list-style-type: none"> • CE marking • UL approval 	Yes Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259
<ul style="list-style-type: none"> • CSA approval • ATEX 	Yes; CSA 22.2 60950-1 Yes; IECEx Ex ec IIC T4 Gc; ATEX (EX) II 3G Ex ec IIC T4 Gc
certificate of suitability <ul style="list-style-type: none"> • IECEx 	Yes
EMC	
standard <ul style="list-style-type: none"> • for emitted interference • for interference immunity 	EN 61000-6-3 EN 61000-6-2
environmental conditions	
ambient temperature <ul style="list-style-type: none"> • during operation • during transport • during storage 	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category / acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • at input • at output • for signaling contact • for auxiliary contacts 	Push-in 24V1, 24V2: push-in for 0.5 ... 16 mm ² ; 0V1, 0V2: push-in for 0.5 ... 4 mm ² 1 - 4: push-in for 0.5 ... 4 mm ² 13, 14: push-in for 0.2 ... 1.5 mm ² RST: push-in for 0.2 ... 1.5 mm ²
width / of the enclosure	45 mm
height / of the enclosure	135 mm
depth / of the enclosure	125 mm
installation width	45 mm
mounting height	225 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	45 mm 45 mm 0 mm 0 mm
net weight	0.3 kg
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

