

product type designation



MD720 GSM/GPRS, 2G

modem MD720; GSM/GPRS, 2G mobile radio modem with RS232 interface; for GSM services CSD, GPRS, SMS; Quadband GSM; AT command interface; observe national approvals! autom. GPRS connection setup; incl. gender changer for RS232/PPI adapter

transfer rate	
transfer rate	
<ul style="list-style-type: none"> for GSM transmission 	9600 bit/s
<ul style="list-style-type: none"> for GPRS transmission / with downlink / maximum 	54 kbit/s
<ul style="list-style-type: none"> for GPRS transmission / with uplink / maximum 	42 kbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment 	1
<ul style="list-style-type: none"> for internal network 	1
<ul style="list-style-type: none"> for external network 	1
number of electrical connections	
<ul style="list-style-type: none"> for external antenna(s) 	1
<ul style="list-style-type: none"> for power supply 	1
type of electrical connection	
<ul style="list-style-type: none"> for internal network 	9 pin Sub D
<ul style="list-style-type: none"> for external network 	SMA antenna socket (50 ohms)
<ul style="list-style-type: none"> for external antenna(s) 	SMA antenna socket (50 ohms)
<ul style="list-style-type: none"> for power supply 	4-pole terminal strip
WAN connection	
type of wireless network / is supported	GSM
type of mobile wireless service / is supported	GPRS
operating frequency / for GSM transmission	850 MHz, 900 MHz, 1800 MHz, 1900 MHz
type of GPRS time slot method / multislots class 10	Yes
supply voltage, current consumption, power loss	
supply voltage / rated value	24 V
supply voltage / rated value	12 ... 30
type of voltage / of the supply voltage	DC
consumed current / at rated supply voltage / maximum	355 mA
power loss [W]	
<ul style="list-style-type: none"> typical 	3.4 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	-20 ... +60 °C
<ul style="list-style-type: none"> during storage 	-25 ... +85 °C
relative humidity / at 25 °C / during operation / maximum	95 %
protection class IP	IP30

design, dimensions and weights	
design	compact
depth	90 mm
height	100 mm
width	30 mm
net weight	150 g
fastening method	
<ul style="list-style-type: none"> • 35 mm top hat DIN rail mounting • wall mounting 	Yes Yes
product functions / management, configuration, engineering	
product function	
<ul style="list-style-type: none"> • CLI • web-based management • MIB support 	No No No
protocol / is supported	
<ul style="list-style-type: none"> • Telnet • HTTP 	No No
type of configuration	AT commands
standards, specifications, approvals	
standard	
<ul style="list-style-type: none"> • for EMC • for hazardous zone • for safety / from CSA and UL • for emitted interference • for interference immunity 	EN 61000-6-2, EN 61000-6-4, EN 55022, EN 55024, EN 301 489-1, EN 301 489-7 II 3 G Ex nA IIC T4 Gc UL 60950 EN 55022, EN 61000-6-4 EN 55024, EN 61000-6-2
certificate of suitability	CE conformance declaration
<ul style="list-style-type: none"> • CE marking 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>

last modified:

12/16/2020 