




SCALANCE XC216-4C manageable Layer 2 IE switch; IEC 62443-4-2 certified; 12x 10/100 Mbit/s RJ45 ports; 4x 1000 Mbit/s combo ports (either 1000 Mbit/s/ SFPs or 10/100/1000 Mbit/s RJ45 ports can be used); 1x console port; diagnostics LED; redundant power supply; temperature range -40 °C to +70 °C; assembly: DIN rail/S7 mounting rail/wall; redundancy functions; office features (RSTP, VLAN,...); PROFINET IO device; Ethernet/IP-compliant; C-PLUG slot;

|  |   |
|--|---|
| <b>product type designation</b>  | <b>SCALANCE XC216-4C</b>  |
| <b>transfer rate</b>   |   |
| transfer rate  | 10 Mbit/s, 100 Mbit/s, 1000 Mbit/s  |
| <b>interfaces / for communication / integrated</b>   |   |
| number of electrical connections<br>• for network components or terminal equipment   | 16; RJ45  |
| number of 10/100 Mbit/s RJ45 ports / integrated<br>• with securing collar  | 12  |
| number of 10/100/1000 Mbit/s RJ45 ports / integrated   | 4   |
| number of combo ports / with RJ45 interface for optical plug-in transceiver  | 4; 1000 Mbit/s SFPs   |
| <b>interfaces / for communication / plug-in</b>  |   |
| number of electrical connections<br>• for SFP  | 4; 1000 Mbit/s SFP plug-in transceiver or 100 Mbit/s via SCALANCE SFP991-1(LD) A                        |
| <b>interfaces / other</b>  |   |
| number of electrical connections<br>• for operator console<br>• for signaling contact<br>• for power supply  | 1<br>1<br>1   |
| type of electrical connection<br>• for operator console<br>• for signaling contact<br>• for power supply   | RJ11<br>2-pole terminal block<br>3-pole terminal block, permanently installed                           |
| design of the removable storage<br>• C-PLUG  | Yes   |
| <b>signal inputs/outputs</b>   |   |
| operating voltage / of the signaling contacts<br>• at DC / rated value   | 24 V  |
| <b>supply voltage, current consumption, power loss</b>   |   |
| product component / connection for redundant voltage supply  | Yes   |
| <b>type of voltage / 1 / of the supply voltage</b><br>• supply voltage / 1 / rated value<br>• power loss [W] / 1 / rated value<br>• consumed current / 1 / at rated supply voltage / maximum<br>• supply voltage / 1 / rated value<br>• type of electrical connection / 1 / for power supply<br>• product component / 1 / fusing at power supply input | DC<br>24 V<br>13.2 W<br>0.55 A<br>9.6 ... 31.2 V<br>3-pole terminal block, permanently installed<br>Yes |

|   |  |
|---|--|
| • fuse protection type / 1 / at input for supply voltage  | 3.15 A / 125 V                                       |
| <b>ambient conditions</b>   |  |
| ambient temperature   |  |
| • during operation  | -40 ... +70 °C                                       |
| • during storage  | -40 ... +85 °C                                       |
| • during transport  | -40 ... +85 °C                                       |
| relative humidity   |  |
| • at 25 °C / without condensation / during operation / maximum  | 95 %   |
| protection class IP   | IP20   |
| <b>design, dimensions and weights</b>   |  |
| design  | compact  |
| width   | 140 mm   |
| height  | 150 mm   |
| depth   | 125 mm   |
| net weight  | 1.2 kg   |
| material / of the enclosure   | Polycarbonate (PC-GF10) / pressure die cast aluminum |
| fastening method  |  |
| • 35 mm top hat DIN rail mounting   | Yes  |
| • wall mounting   | No   |
| • S7-300 rail mounting  | Yes  |
| • S7-1500 rail mounting   | Yes  |
| <b>product features, product functions, product components / general</b>                              |  |
| cascading in the case of a redundant ring / at reconfiguration time of <math>\leq 0,3\text{ s}</math> | 50   |
| cascading in cases of star topology   | any (depending only on signal propagation time)      |
| product function / QoS according to DSCP  | Yes  |
| product feature   |  |
| • Cut Through switching method  | No   |
| • Store & Forward switching method  | Yes  |
| <b>product functions / management, configuration, engineering</b>                                     |  |
| product function  |  |
| • CLI   | Yes  |
| • web-based management  | Yes  |
| • MIB support   | Yes  |
| • TRAPs via email   | Yes  |
| • configuration with STEP 7   | Yes  |
| • RMON  | Yes  |
| • SMTP server   | No   |
| • port mirroring  | Yes  |
| • multiport mirroring   | Yes  |
| • CoS   | Yes  |
| • PROFINET IO diagnosis   | Yes  |
| PROFINET conformity class   | B  |
| network load class / according to PROFINET  | 3  |
| product function / switch-managed   | Yes  |
| telegram length / for Ethernet / maximum  | 10240 byte   |
| protocol / is supported   |  |
| • Telnet  | Yes  |
| • HTTP  | Yes  |
| • HTTPS   | Yes  |
| • TFTP  | Yes  |
| • BOOTP   | No   |
| • GMRP  | Yes  |
| • DCP   | Yes  |
| • LLDP  | Yes  |
| • EtherNet/IP   | Yes  |
| • SNMP v1   | Yes  |
| • SNMP v2   | Yes  |
| • SNMP v3   | Yes  |

|   |     |
|---|-----|
| <ul style="list-style-type: none"> <li>IGMP (snooping/querier)</li> </ul>   | Yes |
| identification & maintenance function   |     |
| <ul style="list-style-type: none"> <li>I&amp;M0 - device-specific information</li> </ul>                                | Yes |
| <ul style="list-style-type: none"> <li>I&amp;M1 – higher level designation/location designation</li> </ul>              | Yes |
| <b>product functions / diagnostics</b>  |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>port diagnostics</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>statistics Packet Size</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>statistics packet type</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>error statistics</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>SysLog</li> </ul>  | Yes |
| <b>product functions / VLAN</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>VLAN - port based</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>VLAN - protocol-based</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>VLAN - IP-based</li> </ul>   | No  |
| number of VLANs / maximum   | 257 |
| number of VLANs - dynamic / maximum   | 257 |
| number of VLANs / at ring redundancy (HRP; MRP; standby link)   | 35  |
| protocol / is supported / GVRP  | Yes |
| <b>product functions / DHCP</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>DHCP server</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>DHCP client</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>DHCP Option 82</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>DHCP Option 66</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>DHCP Option 67</li> </ul>  | Yes |
| <b>product functions / redundancy</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>of the PROFINET IO device / is supported / PROFINET system redundancy</li> </ul> | Yes |
| <ul style="list-style-type: none"> <li>ring redundancy</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>High Speed Redundancy Protocol (HRP)</li> </ul>                                  | Yes |
| <ul style="list-style-type: none"> <li>high speed redundancy protocol (HRP) with redundancy manager</li> </ul>          | Yes |
| <ul style="list-style-type: none"> <li>high speed redundancy protocol (HRP) with standby redundancy</li> </ul>          | Yes |
| protocol / is supported / Media Redundancy Protocol (MRP)   | Yes |
| product function  |     |
| <ul style="list-style-type: none"> <li>media redundancy protocol (MRP) with redundancy manager</li> </ul>               | Yes |
| <ul style="list-style-type: none"> <li>Media Redundancy Protocol Interconnection (MRP-I)</li> </ul>                     | Yes |
| <ul style="list-style-type: none"> <li>of the PROFINET IO device / is supported / H-Sync forwarding</li> </ul>          | Yes |
| <ul style="list-style-type: none"> <li>redundancy procedure STP</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>redundancy procedure RSTP</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>redundancy procedure RSTP+</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>redundancy procedure MSTP</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>       | Yes |
| <ul style="list-style-type: none"> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>     | No  |
| <ul style="list-style-type: none"> <li>passive listening</li> </ul>   | Yes |
| protocol / is supported   |     |
| <ul style="list-style-type: none"> <li>LACP</li> </ul>  | Yes |
| <b>product functions / security</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>IEEE 802.1x (radius)</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>broadcast/multicast/unicast limiter</li> </ul>                                   | Yes |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• broadcast blocking</li> </ul>  | Yes   |
| protocol / is supported   |   |
| <ul style="list-style-type: none"> <li>• SSH</li> <li>• SSL</li> </ul>  | Yes<br>Yes  |
| <b>product functions / time</b>   |   |
| product function  |   |
| <ul style="list-style-type: none"> <li>• SICLOCK support</li> <li>• NTP-client</li> <li>• SNTP client</li> </ul>      | Yes<br>Yes<br>Yes   |
| protocol / is supported   |   |
| <ul style="list-style-type: none"> <li>• NTP</li> <li>• SNTP</li> </ul>   | Yes<br>Yes  |
| <b>system modification during operation</b>   |   |
| product function / configuration in RUN via CiR/H-CiR   | Yes   |
| <b>standards, specifications, approvals</b>   |   |
| IT security for industrial automation systems / according to IEC 62443-4-2:2019                                       | Yes   |
| MTBF  | 46 y  |
| reference code  |   |
| <ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> <li>• according to IEC 81346-2:2019</li> </ul> | KF<br>KFE   |
| <b>standards, specifications, approvals / CE</b>  |   |
| certificate of suitability / CE marking   | Yes   |
| product conformity / according to EMC-guideline   | 2014/30/EU  |
| standard  |   |
| <ul style="list-style-type: none"> <li>• for EMC interference emission</li> <li>• for immunity to EMC</li> </ul>      | EN 61000-6-4, EN 50121-12<br>EN 61000-6-2, EN 50121-4   |
| certificate of suitability / RoHS conformity  | Yes; 2011/65/EU   |
| <b>standards, specifications, approvals / hazardous environments</b>  |   |
| certificate of suitability  |   |
| <ul style="list-style-type: none"> <li>• CCC / for hazardous zone according to GB standard</li> </ul>                 | Yes   |
| <b>accessories</b>  |   |
| product extension / optional / C-PLUG   | Yes   |
| <b>further information / internet-Links</b>   |   |
| Internet-Link   |   |
| <ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul>                     | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> |
| <b>last modified:</b>   | 5/11/2022      |