


HSK-M

Metr.-dlouhá



Materiál
Vložka
Tvarové těsnění
O-kroužek
Krytí
Pracovní teplota

poniklovaná mosaz
PA
NBR
NBR
IP 68 – 10 / IP 69K barů
v uvedeném rozsahu sevření
-40 °C – 100 °C



AG	\varnothing mm	GL mm	H mm	 mm	Obj. č
M 12 x 1,5	3 - 6,5	10	19	14	1.609.1200.30
M 12 x 1,5	2 - 5	10	19	14	1.609.1200.31
M 16 x 1,5	4 - 8	10	21	17 / 19	1.609.1600.30
M 16 x 1,5	2 - 6	10	21	17 / 19	1.609.1600.31
M 16 x 1,5	5 - 10	10	22	20	1.609.1611.30
M 20 x 1,5	6 - 12	10	23	22	1.609.2000.30
M 20 x 1,5	5 - 9	10	23	22	1.609.2000.31
M 20 x 1,5	10 - 14	10	24	24	1.609.2016.30
M 25 x 1,5	13 - 18	12	26	30	1.609.2500.30
M 25 x 1,5	9 - 16	12	26	30	1.609.2500.31
M 32 x 1,5	18 - 25	12	31	40	1.609.3200.30
M 32 x 1,5	13 - 20	12	31	40	1.609.3200.31
M 40 x 1,5	22 - 32	15	37	50	1.609.4000.30
M 40 x 1,5	20 - 26	15	37	50	1.609.4000.31
M 50 x 1,5	32 - 38	15	37	57	1.609.5000.30
M 50 x 1,5	25 - 31	15	37	57	1.609.5000.31
M 63 x 1,5	37 - 44	15	38	64 / 68	1.609.6300.30
M 63 x 1,5	29 - 35	15	38	64 / 68	1.609.6300.31

