



CABLE-OPERATED SWITCH METAL ENCLOSURE,  
2X M20X1.5 1NO+2NC,  
LATCHES ACC. TO EN ISO 13850 BUTTON RESET WITH  
YELLOW COVER

#### General technical data:

<b>Product designation</b>		cable-operated switch
<b>Supply voltage</b>		
<ul style="list-style-type: none"> <li>• at 50 Hz / for AC / rated value</li> <li>• maximum</li> </ul>	V	250
<b>Number of indicator lights</b>		1
<b>Type of unlocking device</b>		push-to-unlatch mechanism
<b>Rope length / maximum</b>	m	25
<b>Product component / EMERGENCY STOP device</b>		No
<b>Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750</b>		S
<b>Reference code / according to DIN EN 61346-2</b>		S
<b>Width</b>	mm	52
<b>Height</b>	mm	171
<b>Depth</b>	mm	53.5

#### Enclosure:

<b>Mounting type</b>		screw fixing
<b>Material / of the enclosure</b>		metal
<b>Color / of top part of the enclosure</b>		grey

**Contact:**

Number of NC contacts / for auxiliary contacts

2

Number of NO contacts / for auxiliary contacts

1

Switching function / arresting lock

Yes

**Certificates/ approvals:****General Product Approval****Declaration of Conformity****Shipping Approval****Ambient conditions:**

Protection class IP

IP65

Ambient temperature

- during operating

°C

-25 ... +70

**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**
<http://www.siemens.com/industrial-controls/catalogs>
**Industry Mall (Online ordering system)**
<http://www.siemens.com/industrial-controls/mall>
**Cax online generator**
<http://www.siemens.com/cax>
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<http://support.automation.siemens.com/WW/view/en/3SE7150-1BH00/all>
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3SE7150-1BH00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE7150-1BH00)

last change:

Jan 21, 2013