



SURGE SUPPRESSOR,
SUPPRESSION DIODE DC 12...250V,
F. CONT. RELAYS A. MOTOR CONT. SZ S00,

General technical data:

product brand name		SIRIUS
Product designation		surge suppressor
Size of contactor		S00
Design of the surge suppressor		with diode
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60

Control circuit:

Type of voltage / of the control supply voltage		DC
Control supply voltage / 1		
• for DC		
• Initial rated value	V	12
• Final rated value	V	250

Installation/mounting/dimensions:

mounting position		any
Mounting type		clip-on
Width	mm	28
Height	mm	46

Depth

mm

9

Certificates/approvals:

Certificate of suitability

CE / UL / CSA / CCC

General Product Approval

**Declaration of
Conformity**

Test Certificates



[Special Test
Certificate](#)

Shipping Approval



Shipping Approval

other



[Confirmation](#)



[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator



<http://www.siemens.com/cax>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3RT2916-1DG00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT2916-1DG00





last change:

Nov 4, 2014