



PLUG-IN RELAY, 3 CO CONTACTS, 115V AC, 10A, WIDTH 22.5MM

General technical details:

Supply voltage frequency / for auxiliary and control current circuit / Rated value

• minimum	Hz	50
• maximum	Hz	60

Type of voltage

AC

Control supply voltage

• with AC / at 50 Hz / Rated value		
• minimum	V	115
• maximum	V	115
• with AC / at 60 Hz / Rated value		
• minimum	V	115
• maximum	V	115

Number of NC contacts

• for auxiliary contacts	0
--------------------------	---

Number of NO contacts

• for auxiliary contacts	0
--------------------------	---

Number of CO contacts

• for auxiliary contacts	3
--------------------------	---

Operating current / of the auxiliary contacts

• at DC-13	
------------	--

<ul style="list-style-type: none"> • at 24 V • at AC-15 • at 230 V 	A	8
Design of the switching function	A	5
<ul style="list-style-type: none"> • positively driven 		changeover switch
Switching behavior		No
		monostable

Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / Plug-in socket		No
Width	mm	22.5
Height	mm	28
Depth	mm	35

Certificates/approvals:

General Product Approval



other

[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/LZX:PT370615/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:PT370615

last change:

Sep 22, 2014