

## Snapflex, průmyslový standard, metrická řada

### Snapclíc-DUO-PA

**Metr.**

**Materiál** Polyamid


**Těsnění vložka** NBR

**RoHS**
**Pracovní teplota** -40 °C – 100 °C

**Barva** černá (RAL 9005)

**Upozornění:**

- Závít NPT a dlouhý připojovací závít na poptávku



AG	$\varnothing$ mm	GL mm	H mm	D mm	$\varnothing$ mm	Vhodné pro Snapflex	Obj. č
M 16 x 1,5	5-10	8	42	25	22	16	1.542.1601.50
M 16 x 1,5	3-7	8	42	25	22	16	1.542.1601.51
M 20 x 1,5	10-14	10	46	30	27	20	1.542.2001.50
M 20 x 1,5	7-12	10	46	30	27	20	1.542.2001.51
M 25 x 1,5	13-18	11	50	35	33	25	1.542.2501.50
M 25 x 1,5	9-16	11	50	35	33	25	1.542.2501.51
M 32 x 1,5	18-24	11	60	42	42	32	1.542.3201.50
M 32 x 1,5	13-20	11	60	42	42	32	1.542.3201.51
M 40 x 1,5	22-31	13	60	50	53	40	1.542.4001.50
M 40 x 1,5	20-26	13	60	50	53	40	1.542.4001.51

### Snapclíc-DUO-PA

**PG**

**Materiál** Polyamid


**RoHS**
**Těsnění vložka** NBR

**Pracovní teplota** -40 °C – 100 °C

**Barva** černá (RAL 9005)

**Upozornění:**

- Závít NPT a dlouhý připojovací závít na poptávku



AG	$\varnothing$ mm	GL mm	H mm	D mm	$\varnothing$ mm	Vhodné pro Snapflex	Obj. č
PG 11	5-10	8	42	25	22	16	1.543.1116.14
PG 11	3-7	8	42	25	22	16	1.543.1116.15
PG 16	10-14	10	46	30	27	20	1.543.1620.14
PG 16	7-12	10	46	30	27	20	1.543.1620.15
PG 21	13-16	11	50	35	33	25	1.543.2125.14
PG 21	9-16	11	50	35	33	25	1.543.2125.15
PG 29	18-22	11	60	42	42	32	1.543.2932.14
PG 29	13-20	11	60	42	42	32	1.543.2932.15
PG 36	22-31	13	60	50	53	40	1.543.3640.14
PG 36	20-26	13	60	50	53	40	1.543.3640.15