

V-Ms-Ex-d


Metr., NPT



II 2G 1D Ex d IIC

Mezinárodní certifikáty najdete na str. 176 nebo na internetu: www.hummel.com

Materiál	poniklovaná mosaz
Krytí	IP 68 – 10 bar / IP 69K
O-kroužek	NBR / FPM / VMQ
Pracovní teplota	-20°C – 95°C (NBR) -20°C – 180°C (FPM), -60°C – 180°C (VMQ)



AG	GL mm	H mm	mm	Obj. č Bez o-kroužku	Obj. č NBR -20 °C – 95 °C	Obj. č FPM -20 °C – 180 °C	Obj. č VMQ -60 °C – 180 °C
M 12 x 1,5	16	21	14		1.875.1200.50	1.876.1200.50	1.877.1200.50
M 16 x 1,5	16	20	19		1.875.1600.50	1.876.1600.50	1.877.1600.50
M 20 x 1,5	16	19,5	22		1.875.2000.50	1.876.2000.50	1.877.2000.50
M 25 x 1,5	16	19,5	30		1.875.2500.50	1.876.2500.50	1.877.2500.50
M 32 x 1,5	16	20,5	41		1.875.3200.50	1.876.3200.50	1.877.3200.50
M 40 x 1,5	16	21	46		1.875.4000.50	1.876.4000.50	1.877.4000.50
M 50 x 1,5	16	22	55		1.875.5000.50	1.876.5000.50	1.877.5000.50
M 63 x 1,5	16	22,5	70		1.875.6300.50	1.876.6300.50	1.877.6300.50
NPT 3/8"	16	20	16	1.877.3800.70			
NPT 1/2"	20	23,5	24	1.877.1200.70			
NPT 3/4"	20,5	24	30	1.877.3400.70			
NPT 1"	25	29,5	41	1.877.1000.70			
NPT 1 1/4"	26	31	46	1.877.5400.70			
NPT 1 1/2"	26,5	32,5	55	1.877.6400.70			