

ISOLATOR 32A TRIPLE POLE



Figure similar

Model		
product brand name		SENTRON
Product designation		On/Off switches
Type of light source		Not applicable
Mounting type / for light source		Not applicable
Design of the switching function		Switch disconnecter
General technical data		
Number of poles		3
Short-circuit current rating	kA	10
Protection class		
Protection class IP		Other
Switching capacity		
Switching capacity current		
• Rated value	kA	0.096
Main circuit		
Operating voltage		
• Rated value	V	440
Operating current		
• Rated value	A	32
Color		
• of the lens		Not applicable
Product details		
Product component		

- Signal lamp

No

## Product function

### Product function

- positive opening (acc. to DIN VDE 0113)

No

## Number

Number of NC contacts

0

Number of NO contacts

3

Number of CO contacts

0

## Mechanical Design

Installation depth

mm

70

Number of width units

3

### General Product Approval

### Declaration of Conformity



[other](#)



## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TL13320>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5TL13320/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL13320](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL13320)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

23.02.2015