

RC UNIT FOR MCB 5SY TYPE A (PSE/SSF), T=70MM
0.3-63A 4POLE IFN 0,3A 400V F. SELECTIVE
SWITCH-OFF



Figure similar

Model		
product brand name		SENTRON
Product designation		RCCB unit
Design of the product		Selective

General technical data		
Number of poles		4
Size of installation devices / acc. to DIN 43880		1
Protection against electrical shock		Finger and back-of-hand safe
circuit-breaker / Design		5SM9
Mechanical service life (switching cycles) / typical		10 000
Overvoltage category		III

Supply voltage		
Supply voltage		
<ul style="list-style-type: none"> with AC / Rated value 	V	400
<ul style="list-style-type: none"> for testing equipment / minimum 	V	100

Protection class		
Protection class IP		IP20, if the distribution board is installed, with connected conductors

Dissipation		
Active power loss		
<ul style="list-style-type: none"> for rated value of the current / with AC / in hot operating state / per pole 	W	3

Electricity

Tripping residual current / Rated value	mA	300
rated current I _n / IEC, DIN/VDE / at 40 Cel	A	58.59
Type of fault current		A
Current / with AC / Rated value	A	40
Surge current resistance / Rated value	kA	5

Product details

Product property		
<ul style="list-style-type: none"> • halogen-free 		Yes
<ul style="list-style-type: none"> • silicon-free 		Yes
Product expansion / can be installed / supplementary devices		Yes

Number

Number of test cycles / for environmental testing / acc. to IEC 60068-2-30		28
---	--	----

Connections

Connectable conductor cross-section / stranded		
<ul style="list-style-type: none"> • minimum 	mm ²	1.5
<ul style="list-style-type: none"> • maximum 	mm ²	25
Connectable conductor cross-section / solid		
<ul style="list-style-type: none"> • minimum 	mm ²	1.5
<ul style="list-style-type: none"> • maximum 	mm ²	25
Tightening torque / with screw-type terminals		
<ul style="list-style-type: none"> • minimum 	N·m	2.5
<ul style="list-style-type: none"> • maximum 	N·m	3
Position / of power supply cord		top or bottom

Mechanical Design

Height	mm	90
Width	mm	124
Depth	mm	77
mounting position		any
Installation depth	mm	70
Number of width units		3
Mounting type		DIN rail (REG)
Net weight	g	351

Environmental conditions

Ambient temperature		
<ul style="list-style-type: none"> • minimum 	°C	-25
<ul style="list-style-type: none"> • maximum 	°C	45
<ul style="list-style-type: none"> • during storage / minimum permissible 	°C	-40
<ul style="list-style-type: none"> • during storage / maximum permissible 	°C	75

Certificates

Equipment marking

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

F
F

General Product Approval

Declaration of Conformity



[other](#)



other

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SM26458>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SM26458/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM26458

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

05.05.2015