

## V-N-Ms Metr., PG

Materiál	poniklovaná mosaz
Krytí	IP 54

AG	GL mm	H mm	D mm	Obj. č.	AG	GL mm	H mm	D mm	Obj. č.
M 12 x 1,5	5	7,5	14	1.052.1200.50	PG 7	5	8	14	1.052.0700.01
M 16 x 1,5	5	9,0	18	1.052.1600.50	PG 9	6	9	17	1.052.0900.01
M 20 x 1,5	6,5	9,5	22	1.052.2000.50	PG 11	6	9	20	1.052.1100.01
M 25 x 1,5	7	11,0	28	1.052.2500.50	PG 13,5	6,5	9,5	22	1.052.1300.01
M 32 x 1,5	8	12,0	35	1.052.3200.50	PG 16	6,5	9,5	24	1.052.1600.01
M 40 x 1,5	8,5	13,0	44	1.052.4000.50	PG 21	7	11	30	1.052.2100.01
M 50 x 1,5	9	15,0	54	1.052.5000.50	PG 29	8	12	39	1.052.2900.01
M 63 x 1,5	10	16,0	67	1.052.6300.50	PG 36	9	15	50	1.052.3600.01
					PG 42	10	16	57	1.052.4200.01
					PG 48	10	16	64	1.052.4800.01

## V-N-Ms-SD Metr., PG

Materiál	poniklovaná mosaz
O-kroužek	NBR
Krytí	IP 68
Pracovní teplota	-40 °C – 80 °C

**Upozornění:**

- NPT závity na dotaz
- Dlouhý závit na poptávku
- Jiný materiál pro O-kroužky na poptávku

AG	GL mm	H mm	D mm	Obj. č.	AG	GL mm	H mm	D mm	Obj. č.
M 12 x 1,5	6,5	9,5	14	1.052.1201.50	PG 7	4,8	8	14	1.052.0701.01
M 16 x 1,5	6	9	20	1.052.1601.50	PG 9	5,5	9	17	1.052.0901.01
M 20 x 1,5	6,5	9,5	24	1.052.2001.50	PG 11	5,5	9	20	1.052.1101.01
M 25 x 1,5	7	11	28	1.052.2501.50	PG 13,5	6	9,5	22	1.052.1301.01
M 32 x 1,5	8	12,5	35	1.052.3201.50	PG 16	6	9,5	24	1.052.1601.01
M 40 x 1,5	8	12	45	1.052.4001.50	PG 21	6,5	11	30	1.052.2101.01
M 50 x 1,5	9	15	55	1.052.5001.50	PG 29	7,5	12	39	1.052.2901.01
M 63 x 1,5	10	16	68	1.052.6301.50	PG 36	9	15	50	1.052.3601.01
					PG 42	10	16	57	1.052.4201.01
					PG 48	10	16	64	1.052.4801.01