

POWER SUPPLY S7-1500 PM1507  
 SIMATIC PM 1507 24 V/8 A STABILIZED POWER SUPPLY FOR  
 SIMATIC S7-1500 INPUT: 120/230 V AC OUTPUT: 24 V/8 A DC



Input	
Input	1-phase AC
Supply voltage	
<ul style="list-style-type: none"> <li>• 1 at AC Rated value</li> <li>• 2 at AC Rated value</li> <li>• Note</li> </ul>	120 V 230 V Automatic range selection
Input voltage	
<ul style="list-style-type: none"> <li>• 1 at AC</li> <li>• 2 at AC</li> </ul>	85 ... 132 V 170 ... 264 V
Wide-range input	No
Overvoltage resistance	2.3 × Vin rated, 1.3 ms
Mains buffering at lout rated, min.	20 ms; at Vin = 93/187 V
Rated line frequency	50 ... 60 Hz
Rated line range	45 ... 65 Hz
Input current	
<ul style="list-style-type: none"> <li>• at rated input voltage 120 V</li> <li>• at rated input voltage 230 V</li> </ul>	3.7 A 1.7 A
Switch-on current limiting (+25 °C), max.	62 A
Duration of inrush current limiting at 25 °C	

• maximum	3 ms
$I^2t$ , max.	12 A <sup>2</sup> ·s
Built-in incoming fuse	T 6.3 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: 16 A characteristic B or 10 A characteristic C

## Output

Output	Controlled, isolated DC voltage
Rated voltage $V_{out}$ DC	24 V
Total tolerance, static $\pm$	1 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
Product function Output voltage adjustable	No
Status display	LED green for 24 V OK; LED red for error; LED yellow for stand-by
On/off behavior	No overshoot of $V_{out}$ (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	10 ms
Rated current value $I_{out}$ rated	8 A
Current range	0 ... 8 A
Active power supplied typical	192 W
Short-term overload current	
• on short-circuiting during the start-up typical	35 A
• at short-circuit during operation typical	35 A
Duration of overloading capability for excess current	
• on short-circuiting during the start-up	70 ms
• at short-circuit during operation	70 ms
Parallel switching for enhanced performance	Yes; Parallel switching of 3 A and 8 A possible, devices must be switched on at the same time, max. 75% per device with I-load
Numbers of parallel switchable units for enhanced performance	2

## Efficiency

Efficiency at $V_{out}$ rated, $I_{out}$ rated, approx.	90 %
Power loss at $V_{out}$ rated, $I_{out}$ rated, approx.	21 W

## Closed-loop control

Dynamic mains compensation ( $V_{in}$ rated $\pm 15$ %), max.	0.1 %
Dynamic load smoothing ( $I_{out}$ : 50/100/50 %), $U_{out} \pm$ typ.	2 %
Dynamic load smoothing ( $I_{out}$ : 10/90/10 %), $U_{out} \pm$ typ.	3 %
Load step setting time 10 to 90%, typ.	5 ms

Load step setting time 90 to 10%, typ.	5 ms
Setting time maximum	5 ms

### Protection and monitoring

Output overvoltage protection	Additional control loop, limitation (closed loop control) at < 28.8 V
Current limitation	8.4 ... 9.6 A
Current limitation, typ.	9 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Overload/short-circuit indicator	-

### Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178 and EN 61131-2
Protection class	Class I
Leakage current <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul>	3.5 mA 1.3 mA
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289
Explosion protection	IECEx Ex nA nC IIC T3 Gc; ATEX (EX) II 3G Ex nA nC IIC T3 Gc; cULus (ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T3, File E330455
Certificate of suitability IECEx	Yes
Certificate of suitability NEC Class 2	No
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	Yes
Marine approval	GL, DNV
Degree of protection (EN 60529)	IP20

### EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

### Operating data

Ambient temperature <ul style="list-style-type: none"> <li>• during operation</li> <li>— Note</li> <li>• during transport</li> <li>• during storage</li> </ul>	0 ... 60 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

### Mechanics

Connection technology	Screw-/spring clamp connection
Connections <ul style="list-style-type: none"> <li>• Supply input</li> <li>• Output</li> </ul>	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup> L+, M: 2 spring-loaded terminals each for 0.5 to 2.5 mm <sup>2</sup>
Product function <ul style="list-style-type: none"> <li>• removable terminal at input</li> <li>• removable terminal at output</li> </ul>	Yes Yes
Width of the enclosure	75 mm
Height of the enclosure	147 mm
Depth of the enclosure	129 mm
Weight, approx.	0.74 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Installation	Can be mounted onto S7-1500 rail
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)