

RESIDUAL CURRENT MONITOR ANALOG, TYPE A
IDN 0,03A 5A 0,02 5 SEC



Model		
product brand name		SENTRON
Type of voltage / for actuation		AC
Main circuit		
Operating frequency / Rated value		
• minimum	Hz	50
• maximum	Hz	60
Operating voltage / Rated value		
• maximum	V	276
Control current		
Control supply voltage		
• at AC / at 50 Hz / Rated value / minimum	V	184
• at AC / at 50 Hz / Rated value / maximum	V	276
• at AC / at 60 Hz / Rated value / minimum	V	184
• at AC / at 60 Hz / Rated value / maximum	V	276
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0

Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1

Suitability

Suitability for operation		For AC networks
---------------------------	--	-----------------

Product function

Product function / Fault storage		Yes
----------------------------------	--	-----

Connections

Type of electrical connection		screw-type terminals
-------------------------------	--	----------------------

Mechanical Design

Height	mm	85
Width	mm	36
Depth	mm	68
Net weight	g	179

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SV80006KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SV80006KK/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SV80006KK

CAX-Online-Generator


<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:



25.08.2015