

PIN BUSBAR, 16 SQMM CONNECTION: 5X(2-PHASE+HS/FS) SAFE-TO-TOUCH




Figure similar

Model		
product brand name		SENTRON
Product designation		Pin busbar
Design of the product		16mm ² ,5X(2PH+HS/FS)
Busbar design		laminated
General technical data		
Surface processing / tin-plated		No
Main circuit		
Operating current / Rated value	A	80
Product details		
Product property / flexible		No
Mechanical Design		
Width	mm	7.5
Length	mm	209.5
Thickness / of busbar	mm	19
Net weight	g	83.62
Material / of the busbar		SF-Cu F 24



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5ST3642>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5ST3642/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3642

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



¹⁾ Pin spacings in MW (Modular widths, 1 MW = 18 mm).

last modified:

12.10.2015