

NEOZED FUSE LINK 400V GL, SIZE D02, 63A IN FOLDING BOX



Figure similar

Model		
product brand name		SENTRON
Product variations		Pack of 10
Design of the fuse link		NEOZED fuse links
General technical data		
Size of fuse system / acc. to DIN EN 60269-1		D02
Operating class of the fuse link		gG
circuit-breaker / Design		5SE2
Supply voltage		
• at AC / Rated value	V	400
Protection class		
Protection class IP		IP20, with connected conductors
Switching capacity		
Switching capacity current / acc. to IEC 60947-2 / Rated value	kA	50
Dissipation		
Active power loss		

- for rated value of the current / at AC / in hot operating state / per pole

W	4.2
---	-----

### Electricity

rated current I <sub>n</sub> / IEC, DIN/VDE / at 40 Cel	A	59.85
Current / at AC / Rated value	A	63

### Appearance

Color coding of the fuse link		copper
-------------------------------	--	--------

### Mechanical Design

mounting position		Any, preferably vertical
Net weight	g	15

### Environmental conditions

<b>Ambient temperature</b>		
• minimum	°C	-5
• maximum	°C	40
<b>Environmental category</b>		Up to 45°C at 95 % rel. humidity

<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>Test Certificates</b>
---------------------------------	----------------------------------	--------------------------



ÖVE



VDE



EG-Konf.

[Typprüfbescheinigung/Werkszeugnis](#)

[sonstig](#)

<b>Test Certificates</b>	<b>other</b>
--------------------------	--------------

[spezielle Prüfbescheinigung](#)  
[n](#)

[Umweltbestätigung](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SE2363>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5SE2363/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5SE2363](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SE2363)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

15.10.2015