


UKONČOVACÍ MATERIÁL - NEIZOLOVANÉ KONCOVKY

Neizolované koncovky typ „KE“.

Neizolované dutinky typ „KE“ jsou vyrobeny z elektrolytické mědi a jsou pocínované.

KE



Průřez vodiče (mm)	Objednací číslo	Rozměry (mm)			Balení
		Ø	L	C	
0,5	KE 506 ST *	1,0	6,0	2,1	50000/500
	KE 508 ST	1,0	8,0	2,1	50000/500
0,75	KE 7506 ST *	1,2	6,0	2,3	50000/500
	KE 7508 ST	1,2	8,0	2,3	50000/500
1	KE 106 ST *	1,4	6,0	2,5	25000/500
	KE 110 ST *	1,4	10,0	2,5	25000/500
1,5	KE 1508 ST *	1,8	7,0	2,8	25000/500
	KE 1510 ST *	1,8	10,0	2,8	25000/500
2,5	KE 2508 ST *	2,3	7,0	3,4	25000/500
	KE 2510 ST *	2,3	10,0	3,4	15000/500
4	KE 410 ST *	2,8	9,0	4,0	12500/500
	KE 412 ST *	2,8	12,0	4,0	12500/500
6	KE 610 ST *	3,5	10,0	4,7	10000/500
	KE 612 ST *	3,5	12,0	4,7	7500/500
	KE 616 ST *	3,5	15,0	4,7	5000/500
10	KE 1016 ST *	4,5	15,0	5,8	4000/250
16	KE 1616 ST *	5,8	15,0	7,5	3000/250
25	KE 25015 ST	7,3	15,0	9,5	1500/100
	KE 25018 ST *	7,3	18,0	9,5	1500/100
35	KE 35012 ST	8,3	12,0	11,0	1500/100
	KE 35015 ST	8,3	15,0	11,0	1500/100
	KE 35018 ST *	8,3	18,0	11,0	1000/100

* dle DIN 46228/1