

# UKONČOVACÍ MATERIÁL - IZOLOVANÉ KONCOVKY

Izolované a plně izolované koncovky s polykarbonátovou izolací.



**RF-F BF-F GF-F**

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	<b>RF-F 305</b>	2,8 × 0,5	3000/100
	0,25 - 1,5 (22-16)	<b>RF-F 308<sup>✕</sup></b>	2,8 × 0,8	3000/100
	0,25 - 1,5 (22-16)	<b>RF-F 405</b>	4,8 × 0,5	2500/100
	0,25 - 1,5 (22-16)	<b>RF-F 408</b>	4,8 × 0,8	2500/100
	0,25 - 1,5 (22-16)	<b>RF-F 608</b>	6,35 × 0,8	2000/100
	1,5 - 2,5 (16-14)	<b>BF-F 405</b>	4,8 × 0,5	2500/100
	1,5 - 2,5 (16-14)	<b>BF-F 408</b>	4,8 × 0,8	2500/100
	1,5 - 2,5 (16-14)	<b>BF-F 608</b>	6,35 × 0,8	1500/100
	4 - 6 (12-10)	<b>GF-F 608</b>	6,35 × 0,8	1000/100

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	<b>RF-F 305P</b>	2,8 × 0,5	3000/100
	0,25 - 1,5 (22-16)	<b>RF-F 308P<sup>✕</sup></b>	2,8 × 0,8	3000/100
	0,25 - 1,5 (22-16)	<b>RF-F 405P</b>	4,8 × 0,5	2500/100
	0,25 - 1,5 (22-16)	<b>RF-F 408P</b>	4,8 × 0,8	2500/100
	0,25 - 1,5 (22-16)	<b>RF-F 608P</b>	6,35 × 0,8	2000/100
	1,5 - 2,5 (16-14)	<b>BF-F 405P</b>	4,8 × 0,5	2500/100
	1,5 - 2,5 (16-14)	<b>BF-F 408P</b>	4,8 × 0,8	2500/100
	1,5 - 2,5 (16-14)	<b>BF-F 608P</b>	6,35 × 0,8	1500/100
	4 - 6 (12-10)	<b>GF-F 608P</b>	6,35 × 0,8	1000/100

<sup>✕</sup> nemá certifikaci UL.

Izolované a plně izolované koncovky s polykarbonátovou izolací.



**RF-M BF-M GF-M**

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	<b>RF-M 608</b>	6,35 × 0,8	3000/100
	1,5 - 2,5 (16-14)	<b>BF-M 608</b>	6,35 × 0,8	2500/100
	4 - 6 (12-10)	<b>GF-M 608</b>	6,35 × 0,8	1000/100

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	<b>RF-M 608P<sup>✕</sup></b>	6,35 × 0,8	1000/100
	1,5 - 2,5 (16-14)	<b>BF-M 608P<sup>✕</sup></b>	6,35 × 0,8	1000/100

<sup>✕</sup> nemá certifikaci UL.