

UKONČOVACÍ MATERIÁL - IZOLOVANÉ KONCOVKY

Izolované a plně izolované koncovky s polykarbonátovou izolací.



RF-F BF-F GF-F

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	RF-F 305	2,8 × 0,5	3000/100
	0,25 - 1,5 (22-16)	RF-F 308[‡]	2,8 × 0,8	3000/100
	0,25 - 1,5 (22-16)	RF-F 405	4,8 × 0,5	2500/100
	0,25 - 1,5 (22-16)	RF-F 408	4,8 × 0,8	2500/100
	0,25 - 1,5 (22-16)	RF-F 608	6,35 × 0,8	2000/100
	1,5 - 2,5 (16-14)	BF-F 405	4,8 × 0,5	2500/100
	1,5 - 2,5 (16-14)	BF-F 408	4,8 × 0,8	2500/100
	1,5 - 2,5 (16-14)	BF-F 608	6,35 × 0,8	1500/100
	4 - 6 (12-10)	GF-F 608	6,35 × 0,8	1000/100

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	RF-F 305P	2,8 × 0,5	3000/100
	0,25 - 1,5 (22-16)	RF-F 308P[‡]	2,8 × 0,8	3000/100
	0,25 - 1,5 (22-16)	RF-F 405P	4,8 × 0,5	2500/100
	0,25 - 1,5 (22-16)	RF-F 408P	4,8 × 0,8	2500/100
	0,25 - 1,5 (22-16)	RF-F 608P	6,35 × 0,8	2000/100
	1,5 - 2,5 (16-14)	BF-F 405P	4,8 × 0,5	2500/100
	1,5 - 2,5 (16-14)	BF-F 408P	4,8 × 0,8	2500/100
	1,5 - 2,5 (16-14)	BF-F 608P	6,35 × 0,8	1500/100
	4 - 6 (12-10)	GF-F 608P	6,35 × 0,8	1000/100

[‡] nemá certifikaci UL.

Izolované a plně izolované koncovky s polykarbonátovou izolací.



RF-M BF-M GF-M

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	RF-M 608	6,35 × 0,8	3000/100
	1,5 - 2,5 (16-14)	BF-M 608	6,35 × 0,8	2500/100
	4 - 6 (12-10)	GF-M 608	6,35 × 0,8	1000/100

	Průřez vodiče (mm) (AWG)	Objednáací číslo	Kolík (mm)	Balení
	0,25 - 1,5 (22-16)	RF-M 608P[‡]	6,35 × 0,8	1000/100
	1,5 - 2,5 (16-14)	BF-M 608P[‡]	6,35 × 0,8	1000/100

[‡] nemá certifikaci UL.