



G FUSE LINK DIN 41662 TIME-LAG LOW BREAKING
CAPACITY RATED UNINT. CURRENT 6.3A



Figure similar

Model		
product brand name		SETRON
Product designation		G fuse link
Design of the product		time-lag (T)
Type of miniature fuse		glass fuse
General technical data		
Melting characteristics		slow acting (T)
Main circuit		
Operating voltage / rated value	V	250
Operating current / rated value	A	6.3
Display and operation		
Product component / visual fault warning		No

General Product Approval	Declaration of Conformity	Test Certificates	other
	 EG-Konf.	sonstig	Umweltbestätigung

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA18227EF85>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA18227EF85/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA18227EF85

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

22.03.2016