

OUTPUT COUPLING DEVICE, RELAY COUPLER, 1
CO CONTACT 24V AC/DC WIDTH 6.2MM SCREW
TERMINAL



Figure similar

product brand name		SIRIUS
Product designation		Coupling relays with relay output (not plug-in)

General technical data:		
Product component Plug-in socket		No
Product component Relay output		Yes
Product component semi-conductor output		No
Consumed active power	W	0.3
Insulation voltage for overvoltage category III according to IEC 60664		
• with degree of pollution 3 rated value	V	300
Type of voltage		AC/DC
maximum permissible voltage for safe isolation		
• between control and auxiliary circuit	V	300
Percental drop-out voltage related to the input voltage	%	10
Thermal current	A	6
Opening delay		
• at AC	ms	14

• at DC	ms	13
Closing delay		
• at AC	ms	12
• at DC	ms	6
Design of the switching function positively driven		No
Operating frequency maximum	1/h	72 000
Electrical endurance (switching cycles)		
• at AC-15 at 230 V typical		100 000
Mechanical service life (switching cycles) typical		10 000 000
Shock resistance acc. to IEC 60068-2-27		sinusoidal half-wave 15g / 11 ms
Vibration resistance acc. to IEC 60068-2-6		6 ... 150 Hz: 2 g
Surge voltage resistance rated value	kV	4
Protection class IP		IP20
Equipment marking		
• acc. to DIN EN 81346-2		K
• acc. to DIN EN 61346-2		K
Display version LED		Yes

Control circuit/ Control:

Operating range factor control supply voltage rated value		
• at AC		1.25 to 0.8
• at DC		0.8 to 1.25
		0.8 ... 1.25

Auxiliary circuit:

Type of switching contact		Changeover contact
Material of switching contacts		AgSnO2
Type of electrical connection for auxiliary and control current circuit		screw-type terminals
Contact reliability of auxiliary contacts		one incorrect switching operation of 100 million switching operations (17 V, 5 mA)
Number of CO contacts for auxiliary contacts		1
Operating current of auxiliary contacts		
• at DC-13 at 24 V	A	1
• at DC-13 at 125 V	A	0.2
• at AC-15 at 24 V	A	3
• at AC-15 at 250 V	A	3
• at DC-13 at 250 V	A	0.1

Short-circuit:

Design of the fuse link for short-circuit protection of the auxiliary switch required		fuse gG: 4 A
--	--	--------------

Inputs/ Outputs:

Property of the output Short-circuit proof		No
Ampacity of the output relay		
• at AC-15 at 250 V at 50/60 Hz	A	3
• at DC-13		
— at 24 V	A	1
— at 125 V	A	0.2
— at 250 V	A	0.1

Electromagnetic compatibility:		
EMC emitted interference acc. to IEC 60947-1		ambience A (industrial sector)
EMI immunity acc. to IEC 60947-1		corresponds to degree of severity 3
Field-bound parasitic coupling acc. to IEC 61000-4-3		10 V/m
Conducted interference		
• due to conductor-earth surge acc. to IEC 61000-4-5		2 kV
• due to conductor-conductor surge acc. to IEC 61000-4-5		1 kV
• due to burst acc. to IEC 61000-4-4		2 kV
Electrostatic discharge acc. to IEC 61000-4-2		6 kV contact discharge / 8 kV air discharge

Connections/ Terminals:		
Type of connectable conductor cross-sections		
• solid		1x (0.25 ... 2.5 mm ²)
• finely stranded with core end processing		1x (0.25 ... 1.5 mm ²)
• at AWG conductors solid		1 x (20 ... 14)
Connectable conductor cross-section		
• solid	mm ²	0.25 ... 2.5
• finely stranded with core end processing	mm ²	0.25 ... 1.5
AWG number as coded connectable conductor cross section		
• solid		20 ... 14
Tightening torque with screw-type terminals	N·m	0.5 ... 0.6
Wire length		
• at AC maximum	m	500
• at DC maximum	m	1 000

Installation/ mounting/ dimensions:		
Mounting position		any
Mounting type		snap-on mounting
Height	mm	93
Width	mm	6.2
Depth	mm	72.5
Required spacing		
• with side-by-side mounting		
— forwards	mm	0

— Backwards	mm	0
— upwards	mm	0
— downwards	mm	0
— at the side	mm	0
• for grounded parts		
— forwards	mm	0
— Backwards	mm	0
— upwards	mm	0
— downwards	mm	0
— at the side	mm	0
• for live parts		
— forwards	mm	0
— Backwards	mm	0
— upwards	mm	0
— downwards	mm	0
— at the side	mm	0

Ambient conditions:

Installation altitude at height above sea level maximum	m	2 000
Ambient temperature		
• during operation	°C	-25 ... +60
• during storage	°C	-40 ... +85
• during transport	°C	-40 ... +85
Relative humidity during operation	%	10 ... 95

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ3018-1AB00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3018-1AB00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ3018-1AB00&lang=en



last modified:

07/08/2016