



Model		
product brandname		SETRON
Main circuit		
Operating frequency / rated value		
• minimum	Hz	50
• maximum	Hz	60
Operating voltage / rated value		
• maximum	V	720
Control current		
Control supply voltage		
• at AC / at 50 Hz / rated value / maximum	V	720
• at AC / at 60 Hz / rated value / maximum	V	720
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Suitability		

Suitability for operation		For AC networks
---------------------------	--	-----------------

Product function

Product function / Fault storage		No
----------------------------------	--	----

Connections

Type of electrical connection		screw-type terminals
-------------------------------	--	----------------------

Mechanical Design

Height	mm	33
Width	mm	299
Depth	mm	284
Net weight	g	1 753

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SV8706-0KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SV8706-0KK/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8706-0KK

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

09/22/2016