

SHUNT TRIP DC 24-60V FOR MCB ACC.UL489



Model	
product brandname	SETRON
Product designation	Shunt trip
Design of the product	Mountable
Design of the product / factory mounted	No
Main circuit	
Operating voltage / rated value	60 V
Control current	
Type of voltage / of control voltage	AC/DC
Product details	
Product extension	shunt trip
• can be mounted	Circuit breaker
Number	
Number of fault signal contacts	0
Number of NC contacts	0
Number of NO contacts	0
Number of CO contacts	0

Mechanical Design

Height	110 mm
Width	18 mm
Depth	70 mm
Number of width units	1
Net weight	118 g

General Product Approval

Declaration of Conformity



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5ST3031-0HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5ST3031-0HG/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3031-0HG

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



