

LV HRC fuse link, NH000, In: 63 A, gG, Un AC: 400 V, Combination indicator, insulated grip lugs



Figure similar

Model	
product brandname	SETRON
Product designation	LV HRC fuse link
Design of an identification indicator	Combination alarms
Design of the switching contact	Non-corroding, silver-plated
Design of the fuse link	LV HRC fuse link
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH000
Operating class of the fuse link	gG
circuit-breaker / Design	3NA6
Supply voltage	
• at AC / rated value	400 V
Protection class	
Protection class IP	IP20, with connected conductors
Switching capacity	
Switching capacity current	

- acc. to IEC 60947-2 / rated value 120 kA

### Dissipation

#### Power loss [W]

- for rated value of the current / at AC / in hot operating state / per pole 4.36 W

### Electricity

- rated current  $I_n$  / IEC, DIN/VDE / at 40 Cel 59.85 A
- Current / at AC / rated value 63 A

### Mechanical Design

- Mounting position Any, preferably vertical
- Net weight 129 g

### Environmental conditions

#### Ambient temperature

- minimum -5 °C
- maximum 40 °C
- during storage / Note Air humidity 90% at 20 °C

- Environmental category -20 to +50 at 95% relative humidity

### Certificates

#### Equipment marking

- acc. to DIN EN 61346-2 F
- acc. to DIN EN 81346-2 F

General Product Approval	Test Certificates	Shipping Approval	other
	<a href="#">spezielle Prüfbescheinigung</a> <a href="#">n</a>	<a href="#">sonstig</a>	<a href="#">sonstig</a>



### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NA6822-4>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NA6822-4/all>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA6822-4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA6822-4)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

