

SITOR fuse link, with blade contacts, NH1, In: 315 A, gS, Un AC: 690 V, Un DC: 250 V, Front indicator



Figure similar

Model	
product brandname	SETRON
Design of an identification indicator	front indicator
Design of the fuse link	SITOR, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH1
Operating class of the fuse link	gS
circuit-breaker / Design	3NE
Varying load factor (WL)	1
Supply voltage / at DC	250 V
Switching capacity	
Switching capacity current	
<ul style="list-style-type: none"> acc. to IEC 60947-2 / rated value 	100 kA
Dissipation	
Power loss [W]	

- for rated value of the current / at AC / in hot operating state / per pole 38 W
- maximum 38 W

Electricity

rated current I _n / IEC, DIN/VDE / at 40 Cel	315 A
Current / at AC / rated value	315 A

Mechanical Design

Mounting position	Any, preferably vertical
--------------------------	--------------------------

Environmental conditions

Ambient temperature	
• minimum	-20 °C
• maximum	50 °C
Environmental category	-20 to +50 at 95% relative humidity

Certificates

Equipment marking	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval

Declaration of Conformity

other



[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1230-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NE1230-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1230-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

