

A17-M *Cable type: extra-flexible copper, Maximum section: 70 mm²*

Minimum section

 70 mm²

Maximum section

 70 mm²


Type	Ø Stud mm	Øi mm	B mm	M mm	N mm	L mm	d mm	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
A17-M6	6 mm	13 mm	23 mm	8 mm	7 mm	45 mm	6.4 mm	200	50	13 mm
A17-M8	8 mm	13 mm	23 mm	9 mm	8 mm	47 mm	8.4 mm	150	50	13 mm
A17-M10	10 mm	13 mm	23 mm	11 mm	10 mm	51 mm	10.5 mm	150	50	13 mm
A17-M10/19	10 mm	13 mm	19 mm	11 mm	10 mm	51 mm	10.5 mm	200	50	13 mm
A17-M12	12 mm	13 mm	23 mm	14 mm	12 mm	56 mm	13.2 mm	150	50	13 mm
A17-M14	14 mm	13 mm	25 mm	15.5 mm	12 mm	57.5 mm	15 mm	150	25	13 mm
A17-M16	16 mm	13 mm	27 mm	16.5 mm	13.5 mm	60 mm	17 mm	150	25	13 mm

Products used together

Accessories

INSULATED COVERS ES

ES19-BK	ES19-BR	ES19-BU
ES19-GN	ES19-GY	ES19-PK
ES19-RE	ES19-WH	ES19-YE