

WADI-A-FPM PG

RoHS

Materiál	poniklovaná mosaz
Vložka	FPM
O-kroužek	FPM
Krytí	IP 68
Pracovní teplota	-25 °C – 200 °C

AG	∅ mm	GL mm	H mm	mm	Obj. č
PG 7	5-7	6	16	14	1.106.0700.80
PG 9	6-8	6	17	18	1.106.0900.80
PG 9	7-10	6	17	18	1.106.0901.80
PG 11	6-8	6	20	18	1.106.1100.80
PG 11	7-10	6	20	18	1.106.1101.80
PG 11	8-12	6	20	18	1.106.1102.80
PG 13,5	11-15	6	21	24	1.106.1300.80
PG 16	11-15	6	21	24	1.106.1600.80
PG 21	15-20,5	7,5	22,5	32	1.106.2100.80
PG 29	20-27	8	24	40	1.106.2900.80
PG 36	30-35	8	29	50	1.106.3600.80
PG 42	40-45	10	31	60	1.106.4200.80
PG 48	42-49	11	33	64	1.106.4800.80

WADI-A-FPM s dvoudílným těsněním PG

RoHS

Materiál	poniklovaná mosaz
Vložka	FPM (vystřihnuté)
O-kroužek	FPM
Krytí	IP 68
Pracovní teplota	-25 °C – 200 °C

AG	∅ mm	GL mm	H mm	mm	Obj. č
PG 11	5-12	6	20	18	1.106.1103.80
PG 13,5	8-15	6	21	24	1.106.1301.80
PG 16	8-15	6	21	24	1.106.1601.80
PG 21	11-20,5	7,5	22,5	32	1.106.2101.80
PG 29	18-27	8	24	40	1.106.2901.80
PG 36	25-35	8	29	50	1.106.3601.80
PG 42	35-45	10	30	60	1.106.4201.80
PG 48	38-49	11	33	64	1.106.4801.80

➔ Vhodné příslušenství najdete od str. 73