

MINIZED, Fuse switch disconnecter, D01, 4-pole, 3P+N, In: 16 A, Un AC: 400 V



Figure similar

Model	
product brandname	MINIZED
Product designation	Fuse switch disconnecter
General technical data	
Number of poles	4
Number of poles / Note	3P+N
Size of fuse system / acc. to DIN EN 60269-1	D01
Overvoltage category	4
Voltage	
Surge voltage resistance / rated value	6 kV
Protection class	
Protection class IP	IP20, with connected conductors
Electricity	
Current / at AC / rated value	16 A
Main circuit	

Operating voltage / at AC / rated value	400 V
---	-------

Product details

Product feature / sealable	Yes
----------------------------	-----

Connections

Tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m

Mechanical Design

Height	70 mm
Width	108 mm
Depth	88 mm
Mounting position	any, preferably vertical
Net weight	270 g

Certificates

Equipment marking	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity
---------------------------------	----------------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG7661-0KK16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SG7661-0KK16/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG7661-0KK16

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

